




著名商标

申牌万向轮
SHENPAI Caster®

——SINCE 1993——



产品手册 **工业脚轮V3.0**
CATALOGUE —Industrial Caster

 **江苏申牌万向轮有限公司**
JIANGSU SHENPAI CASTER CO.,LTD

生产基地：江苏省江阴市璜土工业园区姬山路3号

Add: NO.3, Jishan Road, Huangtu Industrial Park Jiangyin, Jiangsu, China

电话(TEL): (+86) 510-86651178

传真(FAX): (+86) 510-86656653

邮编(P.C.): 214445

E-mail: sales@shenpai.com



全国 质量服务热线

800 828 7707

更多详情：请访问

www.shenpai.com

For further information



注意事项：
手册中的部分产品可能存在升级、更新或替换。如有任何疑问请咨询销售部或者授权经销商。您也可以访问www.shenpai.com获取最新产品信息与参数。
Attention:
Some product information in this catalogue may have updated or modified already. Please do not hesitate to contact us if you have any problem.
You could also visit our website www.shenpai.com for latest information.



申牌的价值观：

为客户创造价值
竭力提升产品与服务
止于至善的热情



Value of SHENPAI:

SHare value with customer

ENdeavor to improve

PAssion to perfection

目录 Contents

 信息介绍 Information	公司简介 Brief Introduction 05-06 品牌之路 Brand Reputation..... 07-08 设计与生产 Design & Production 09-10 质量控制 Quality Control..... 11-12 营销网络 Marketing Network 13-14 脚轮选型指南 How to Select a Castor 15-18 轮面材质选择 Selection of Tire Material..... 19-20 定制脚轮 Customized Products 21-22
微型 Micro Duty	01 适用于橱柜、小型设备配套等行业 It is suitable for cabinets, small equipment and other industries.  10A微型..... P25-26 10B微型镀铬..... P27-28 1"-3" 10-50 Kg
轻型 Light Duty	02 适用于纺织厂、美容、医疗、机械制造等多种行业 It is suitable for textile industry, beauty treatment, medical treatment, machinery manufacturing, and many other industries.  15A轻型2"-2.5"..... P31-32 20C轻型3"-4"..... P33-34 2"-4" 35-90 Kg
中型 Medium Duty	03 适用于电子、纺织、机械设备、医疗等行业，使用范围广 It can be widely used in electronics, textile, machinery, medical and other industries.  20A中型..... P37-44 3"-4" 80-160 Kg ANSI BSI bsi.
中重型 Medium-heavy Duty	04 适用于仓储物流、汽车工业、机械制造、医疗等行业 It is suitable for warehousing, logistics, automotive industry, machinery manufacturing, medical and other industries.  25A中空铆接..... P47-48 25X经济款..... P49-50 25D折叠病床款..... P51-52 3"-8" 80-550 Kg ANSI JIS
低重心 Low-barycenter	05 适用于机械设备、仓储物流等行业 It is suitable for machinery, warehousing, logistics and other industries.  30A低重心轻载..... P55-56 30B低重心中载..... P57-58 32A调节轮重载..... P59-60 1.5"-4" 150-1000 Kg
重型 Heavy Duty	06 适用于工厂搬运、仓储物流、机械制造等多种行业 It is suitable for various industries such as plant handling, storage and logistics, machinery manufacturing, and so on.  35A淬火底板..... P63-70 35C经济款..... P71-72 4"-8" 200-500 Kg ANSI

抗冲击型 Shock Resistant	07 高载重、抗冲击性能强，适用行业范围广 High load bearing, strong impact resistance, wide range of industries.  35B重型抗冲击..... P75-78 4"-12" 300-1300 Kg
超重型 Super Heavy Duty	08 适用于重型机械设备、工厂搬运等行业，高品质、高承载 It is suitable for heavy machinery and equipment, factory transportation and other industries, high quality and high load.  40A单轮..... P81-82 40B双轮..... P83-84 3"-12" 1000-5000 Kg
减震轮 Shockproof	09 适用于机械制造、汽车工业等行业，有减震功效 It is suitable for machinery manufacturing, automobile industry and other industries.  45A减震轮..... P87-88 45C经济款..... P89-90 5"-8" 300-550 Kg ANSI
不锈钢轮 Stainless Steel	10 适用于食品加工等行业，防水、防锈 It is suitable for food processing and other industries.  10D轻型..... P93-94 20D中型..... P95-96 35D重型..... P97-98 1.5"-8" 10-350 Kg ANSI SS
特殊用轮 Casters for Speical Occasions	11 适用于餐饮、尼龙转运车、工厂搬运、仓储物流、机械制造、叉车设备等行业 Suitable for catering, nylon transporter, factory handling, warehousing and logistics, machinery manufacturing, forklift equipment and other industries.  56A静音..... P101 65AB充气/发泡..... P102-103 66A脚手架..... P104 70AB叉车用轮..... P105-106 4"-12" 100-800 Kg
附件 Accessories	12 配套使用，达到制动平衡作用 Matching to achieve the balance of braking.  99A美式顶高器..... P107-108 99B日式顶高器..... P107-108 4"-8" ANSI JIS
推车 Hand Cart	13 适用于转运物流车，耐用、静音、轻便、使用便捷 Suitable for transporting logistics vehicles, durable, quiet, light and convenient to use.  99D手推车..... P109-110 150-300Kg
警告 Warning..... P111-112	声明 Statement 申牌万向轮 SHENPAI Caster 此三种商标均为我公司注册商标 Registered trademarks, All rights reserved.

i1 BRIEF INTRODUCTION 公司简介

Jiangsu SHENPAI Caster Co.,LTD is a professional industrial caster manufacturer Since 1993. Located in the centre of Yangtze River Delta, SHENPAI has benefited from the well-developed industry as well as convenient transportation. SHENPAI has 2 production plants total covering 40,000m² area. In these plants, there are more than 200 employees. As an all-round caster Manufactruere, punching, welding, plastic injection, casting, rubber and assembly workshops are running efficiently in these plants.

SHENPAI keeps talents cultivation which has been paying back technical innovation as well as management advantage to our company. SHENPAI has also made some technical cooperation with top universities in Eastern China. We've got dozens of patents and the title of "National high-tech enterprises".

SHENPAI has been improving production equipments such as production automation. The total production efficiency increase around 5% every year, meanwhile, these improvement make production more stable and de-skill the workers. Our company is operated under an ERP system efficiently. For example, the production batch management and material tracing is the overriding support of our brand.

In domestic market, SHENPAI has a nation-wide distribution network with about 150 sales agencies all over China. In international market, casters bearing "SHENPAI" has been sold to 28 countries.



1993

公司成立
第一只脚轮被打上
“申”的记号



2006

首届全国经销商大会
在公司召开



2007

公司获得
“江苏著名商标”称号



2011

公司实施全程
ERP管理系统



2015

公司通过
Bureau Veritas
国际7项审查



2017

公司获得
国家高新技术企业认证

江苏申牌万向轮有限公司成立于1993年，是国内最专业的工业脚轮制造企业之一。公司位于江苏省江阴市，地处长三角中心地区，交通便利，产业链成熟。公司现有两大生产厂区，员工数百名。现有车间执行着冲压、焊接、注胶和装配等生产工艺，全面的生产能力既是成本的有效控制也是品质管理的可靠保障。

公司一直注重人才培养与技术创新，我司现有数位硕士以上技术和管理人才。公司不断组织技术培训，并与德美日韩等国脚轮同行进行技术交流与经验学习。公司与985院校进行深度“产学研”合作。公司持有诸多专利，并荣获国家高新技术企业称号。

公司在生产硬件和管理软件方面也一直在不断升级。公司人均产能每年以高比例递增，对员工的劳动强度和技能要求逐年下降。公司生产全程ERP管理，完善的批次管理和产品追溯体系成为品牌的坚实基础。

在国内市场，各大城市均有申牌授权经销点。完善的经销商网络带来了专业的销售和售后服务。在国际市场，公司拥有数十家合作伙伴，申牌的产品已服务于28个国家和地区，“造国货精品，创世界品牌”已逐渐从口号变为现实。



i2 BRAND REPUTATION

品牌之路

自公司1993成立发展至今，
样册产品也不断升级完善。

Since the establishment and
development of the company
1993, the catalogues of
products have been upgraded
continuously.



品牌价值 源于点滴的积累与不懈的奋斗

2003
ISO9001质量体系认证

2004
无锡市知名商标



2007
江苏省著名商标

2009
脚轮测试实验室建立

2011
公司实施全程ERP管理

2015
公司通过Bureau Veritas国际现场认证


2017
国家高新技术企业
江阴市高性能万向轮工程技术研究中心




The VALUE of brand comes from every single improvement made by our team.

在多年的发展历程中，
公司屡获殊荣，备受认可。

More than
A product,
It's a spirit of
constant improving





i3 DESIGN & PRODUCTION 设计与生产

我们的设计团队具有非常丰富的脚轮行业设计制造经验，能够提供非常专业的脚轮解决方案。

Our technical team is experienced in caster design & manufacturing processes. More than casters, We make perfect solutions.

生产流程 PRODUCTION PROCESS

完美方案

设计评审
DESIGN & REVIEW

模具制造

模具
MOULD

专业制造

自动焊接
ROBOT WELDING

严格标准

质量
QUALITY

物料管控

扫码出入库
CODE-SCAN IN&OUT

便捷快速

发货
DELIVERY

产品溯源 BATCH TRACEABILITY

生产安排任务

任务单流转

装配（喷码）现场

成品包装标签

数据跟踪——每一批原料供应商，每一道工艺操作员工，每一项入库发货，全部可查。

From every batch code, we could find the exact supplier, production staff for every process and distributor of sales.

① 35A67-1816 商牌: 8

②

③

系列 35 A 67-1816

款式

支架编码

轮片编码

产品参数扫描查询

产品生产批次查询

批次: 180406040

全程溯源——每一批产品都有对应的“身份证号”，品质款产品（质保2年）自带喷码。

All products bearing "SHENPAI" has a batch number on its packaging box. Some of them even get a code on bracket, which means 2 year's warranty.

i4 QUALITY CONTROL

质量控制

完善的管理，务实的团队，高效的设备和严格的标准是质量控制的基础，是品牌的生命线。

Advanced management, reliable team, efficient devices and strict standards are the foundation of our quality control.



盐雾试验 / 刹车空载制动测试 / 刹车疲劳试验 / 高低温试验 / 行走测试 / 回转测试 / 拉力试验 / 磨损测试 / 影像测量 /

脚轮行走试验
Turning Test of Universal Caster

塑胶材料实验
Plastic Material Test

电镀件盐雾实验
Electroplated Part Salt Fog Test

塑胶材料冲击实验
Plastic Material Impact Test

每款新产品都经过 **19** 项可靠性验证
19 reliable tests before new product launch.

每年累计 **1000** 多次的产品测试
1000+ different tests will be carried on every year.

自主研发 **6** 项专用检测设备
6 test devices are totally invented by SHENPAI



融合四大标准，
建立最苛刻执行标准—申牌企业标准。
Learn from ANSI, BSI, JIS and GB China,
SHENPAI has made a strict enterprise standard.



American National
Standard Institute
America
美国工业标准



Japanese Industrial
Standards
Japan
日本工业标准



British Standards
Institution
Britain
英国标准协会



GB/T
China
中国国家标准

完善的市场网络为您提供便捷周到的服务
 Hundreds of authorized agencies, Convenient service all over China.

国际市场
 International Market



中国市场
 Domestic Market



日本 JAPAN	印尼 INDONESIA	卡塔尔 QATAR	巴西 BRAZIL
韩国 KOREA	孟加拉 BENGAL	阿联酋 THE UNITED ARAB EMIRATES	阿根廷 ARGENTINA
泰国 THAILAND	印度 INDIA	美国 U.S.A	墨西哥 MEXICO
马来西亚 MALAYSIA	巴基斯坦 PAKISTAN	加拿大 CANADA	澳大利亚 AUSTRALIA
越南 VIETNAM	沙特 SAUDI ARABIA	德国 GERMANY	

华北地区：北京市、天津市、河北省、山西省、内蒙古自治区
 东北地区：辽宁省、吉林省、黑龙江省
 华东地区：上海市、江苏省、浙江省、安徽省、福建省、江西省、山东省
 华中地区：河南省、湖北省、湖南省
 华南地区：广东省、海南省、广西壮族自治区
 西南地区：重庆市、四川省、贵州省、云南省
 西北地区：陕西省、甘肃省、宁夏回族自治区

i6 脚轮选型指南

怎样选择一款适合您需求的脚轮



使用脚轮是为了减轻劳动强度，提高移动效率。那根据您的使用的方式，环境和需求如何正确的选择脚轮，请参考以下几点：

01 计算承载重量

在您决定购买脚轮之前，您首先得知道您购买的这个脚轮需要承载多重，因为脚轮的载重、大小、材质等这些因素都会跟脚轮的价格有直接关系，那么首先该如何计算单个脚轮需要承载的重量呢？

单个脚轮需要承载的重量计算如下

$$T = \frac{E+Z}{n} \times s$$

T= 单个脚轮所需承载能力

n= 计划安装脚轮的数量

E= 运输设备的自重

s= 安全系数

Z= 最大加载量

为了计算出单个脚轮需要承载的重量，您需要提前知道运输设备的自重，运输设备的最大加载量以及计划安装脚轮的数量。


安全系数s会受速度、轮径以及障碍物高度的影响，考虑到标准使用条件（光滑地面，匀速，负载分布均匀，直行，环境温度为15℃~30℃）与实际使用条件存在偏差，所以具体可分为四个类别：

1. 在室内区域手动输送（障碍物高度 < 轮径的5%）：安全系数：1.0至1.5
2. 在室外区域手动输送（障碍物高度 > 轮径的5%）：安全系数：1.5至2.2
3. 在室内区域机动输送（障碍物高度 < 轮径的5%）：安全系数：1.4至2.0
4. 在室外区域机动输送：安全系数：2.0至3.0

使用注意事项：如不地面平，速度高都要把安全系数提高。（参照前面计算载重的内容，安全系数S）

1. 请避免在凹凸严重的地面上使用，在凹凸不平的路面会缩短脚轮寿命。

2. 请避免利用动力对车轮进行超过4km/h的牵引等操作，脚轮会因此受损，可能会造成事故或伤害。



02 选择轮片材质

相信在您确定了脚轮的载重之后，接下来的选择会更加有针对性。申牌V3.0样本根据载重将所有产品依次分为微型、轻型、中型、中重型、重型、超重型及(特殊的45A系列-99D系列)。

脚轮的材质通常有尼龙（浇注尼龙和注塑尼龙），聚氨酯，聚丙烯，酚醛，橡胶，发泡橡胶，人造胶，充气橡胶，铸铁等多种材质。所以不同的使用环境中需要您选择不同材质的脚轮。

铺有地毯、环氧地坪漆、瓷砖或者木质地板的地面

如车间、医院、学校、酒店、办公场地

选择橡胶、人造胶或者聚氨酯等软质材料的脚轮，不仅能有效的起到保护地面的作用，还能最大限度的降低噪音。

铺有水泥、沥青、铁板、或砖头等相对不平整的路面

如车间、工地、公路

选择尼龙、聚氨酯、聚丙烯或者铸铁等硬质材质的脚轮既能满足载重，而且相比软质的材料更加耐用，也更加省力。这里要说的是：聚氨酯和橡胶这两种材料它可以通过调整轮面的硬度做成相应的软质轮或者硬质轮。

比较特殊的环境

如高温环境、酸碱度比较高的环境

如高温环境，可以选择耐高温的酚醛轮或者尼龙轮。

如酸碱度比较高的环境，可以选择耐化学腐蚀性出色的聚氨酯轮或者橡胶轮。

另外在高温高湿、低温、防静电等特殊环境，都可以选择相应材质的脚轮。

具体请参考P19-20《轮面材质的选择》。

03 选择安装方式

脚轮的安装方式常见的有平底安装（螺丝或者焊接），丝杆安装，插轴安装，孔顶安装，夹板安装，不同的运输设备决定了您需要选择不同的安装方式，这里需要关心的就是底板的安装孔距和丝杆、螺杆的直径以及长度。

其他选择

如果您需要的并不是有特殊性能的产品，相信通过前面三个步骤的选择之后您已经有了自己的答案。

前面选择轮片的时候我们讲了不同的使用环境需要您选择不同材质的轮片，这里我们要说的是，同样的轮片材质，不同的轮型结构和大小会给您不同的使用感受，弧形的轮面结构因为与地面的接触面积小，摩擦力小，推行起来相比平面会更加省力，但是弧形的轮面因为与地面的接触面积小，单位面积承受的载荷更多，所以它的额定载重要低。

轮径越大，面对障碍物时的通过性越高，所以更加省力。

滚珠轴承转动灵活，静音，滚针轴承负载高，转动灵活性不及滚珠轴承。

支架的偏心距越大，启动推力越小。

所以选择一款能满足自己需求的脚轮产品，要根据您的需求重点依次选择，有取有舍，才能达到最高的性价比！



i6 HOW TO SELECT A CASTOR FOR YOUR REQUIREMENTS



01 Load Capacity/wheel and Caster Types

Casters are used to reduce labor intensity and improve movement efficiency. How to select the caster according to your usage, environment and requirement

In order to determine the required load capacity of a wheel or caster, the dead weight of transport unit, the maximum additional load and the number of wheels and casters to be used must be known. By using four or more wheels or casters can vary.

The required load capacity can be defined as follows:

$$T = \frac{E+Z}{n} \times s$$

T=Required load capacity of the wheel or caster

E=Dead weight of the transport unit

Z=Maximum additional load

n=Number of wheels or casters used

S=Safety factor

The safety factor S reflects the deviation from the standard application conditions (even floor, walking speed, load must act equally on all wheels or casters, straight travelling, ambient temperatures between 15°C and 30°C). The safety factor is influenced by the speed and the ratio between wheel ø and height of the obstacles. A distinction is drawn between four categories:

1. Indoor manual transport (height of the obstacles < 5% of the wheel ø):
Safety factor: 1.0 to 1.5
2. Outdoor manual transport (height of the obstacles > 5% of the wheel ø):
Safety factor: 1.5 to 2.2
3. Indoor power driven transport (height of the obstacles < 5% of the wheel ø):
Safety factor: 1.4 to 2.0
4. Outdoor power driven transport: Safety factor: 2.0 to 3.0

02

How to select wheel material

I believe that after you have determined the load of the casters, the following choices will be more targeted. All products are classified into mini, light, medium, medium heavy, heavy, super-heavy and (special 45A series -99D series) according to the product manual of SHENPAI V3.0

The casters are usually made of nylon (casting nylon and injection nylon), polyurethane, polypropylene, phenolic, rubber, foam rubber, artificial rubber, inflatable rubber, cast iron and other materials. Therefore, you need to choose casters of different materials in different usage environments.

Where there is carpet, epoxy floor paint, tile or wooden floor, such as workshop, hospital, school, hotel, office space, then the selection of soft materials such as rubber, artificial rubber or polyurethane casters can not only effectively protect the ground, but also minimize noise.

On relatively uneven pavement such as cement, asphalt, iron plate, or brick, such as in workshops, construction sites, highways, then choose rigid casters such as nylon, polyurethane, polypropylene or cast iron to meet the load, and more durable and less labor intensive than soft materials. The point here: polyurethane and rubber are two materials that can be made into a soft or hard wheel by adjusting the hardness of the wheel face.

In addition, special environment, such as high temperature environment, can choose high temperature phenolic or nylon wheels. For example, in an environment with high PH, you can choose a polyurethane wheel or a rubber wheel with excellent chemical corrosion resistance. In addition, high temperature, high humidity, low temperature, anti-static and other special environment, can be selected Casters with corresponding materials. Please refer to P9 for details.

03

Installation options

The installation methods of casters are as follows: flat bottom installation (screw or welding), screw rod installation, shaft installation, hole top installation, plywood installation. Different transportation equipment determines the installation methods you need to choose. What you need to pay attention to is the mounting hole distance of the bottom plate, diameter and length of screw rod and screw rod.

Others

If you don't need a product with special features, you may have an answer after the first three steps.

When we talked about the different of using environment requires you to choose different material of wheel, here we want to say that the same round piece of material, different wheel type structure and size will give you the different use feelings, and wheel surface structure because of small touch with the ground area, low friction, pushing up will be more effort, but arc surface touch with the ground area is small, More loads per unit area, so its rated load is important.

The larger of wheel diameter, the easier pass when facing obstacles, so it is more labor-saving.

Ball bearing rotates flexibly and silent. Needle roller bearing with higher load but less rotational flexibility than ball bearing.

The larger eccentricity of bracket, the smaller of starting thrust.

So choose a castor product that can meet your needs. Must be according to your request that can achieve the highest cost performance!



轮面材质选择 Selection of tire material

轮子特性 Wheel peculiarity						地面材质 Ground material					地面环境 Ground environment															
单轮材质 Wheel material	单轮外径 Diameter	胎面硬度 Hardness	载重KG Load capacity	温度低 Low temperature	温度高 High temperature	沥青地面 Pitch	砖地面 Brick	瓷砖地面 Tiles	地毯 Carpe		水泥地面 Cement	粗糙钢板地面 Coarse steel	平坦钢板地面 Level steel	水磨石地面 Terrazzo	木制地板 Wood	抗动物油脂 Anti-animal oil and fat	抗高腐蚀性药品 Anti-high corrosive drugs	抗轻微腐蚀性药品 Anti-minor corrosive drugs	行走弹性 Flexibility to walk	对地面保护程度 Floor-protection	抗金属碎片性能 Anti-metal craps	抗地面金属废品 Anti-metal waste	防噪声 Anti-noise	抗油脂 Anti-oil and fat	防水性能 Anti-water	
聚丙烯 Polypropylene	PP-N PP-B PP-D PP-S	1"-8"	75D	10 ~ 440	-20	60	F	F	F	G		G	F	F	F	NR	G	NR	F	NR	NR	G	NR	F	G	EG
高强聚丙烯 Modified polypropylene	MP-B	5"-12"	75D	500 ~ 800	-30	90	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	NR	F	G	EG
联体尼龙 Nylon	NL-S NL-N NL-B	1"-3"	75D	15 ~ 1000	-30	90	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	EG
塑芯尼龙 Nylon on plastic core	NLPA	2"-8"	75D	40 ~ 400	-30	90	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	F
注塑尼龙 Nylon	NL-B	3"-5"	75D	1700 ~ 2300	-20	90	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	F
铁芯尼龙 Nylon on cast iron core	NLCB NLCT	6"-12"	75D	600 ~ 5000	-40	100	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	F
铝芯尼龙 Nylon on aluminium core	NLAA	2.5"-4"	75D	300 ~ 450	-40	100	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	F
钢芯尼龙 Nylon on steel plate structure	NLSF	3"-8"	75D	150 ~ 550	-40	100	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	F
高温尼龙 High temperature Nylon	NH-B	3"-8"	85D	100 ~ 430	-25	280	F	F	F	G		G	F	F	F	NR	G	F	G	NR	NR	G	F	F	G	F
塑芯聚氨酯 Polyurethane on plastic core	PUPB PUPS PUPA PUPC PUPF	2"-8"	95A°	35 ~ 450	-40	70	F	EG	EG	G		EG	G	G	G	EG	EG	EG	EG	F	EG	NR	G	G	G	NR
铁芯聚氨酯 Polyurethane on cast iron core	PUCB	4"-12"	95A°	300 ~ 3500	-30	70	F	EG	EG	G		EG	G	G	G	EG	G	EG	G	F	EG	NR	G	G	EG	NR
钢芯聚氨酯 Polyurethane on steel plate structure	PUSF	3"-8"	95A°	120 ~ 450	-30	70	F	EG	EG	G		EG	G	G	G	EG	G	EG	G	F	EG	NR	G	G	EG	NR
铝芯聚氨酯 Polyurethane on aluminium core	PUAA	2.5"-4"	95A°	150 ~ 250	-30	70	F	EG	EG	G		EG	G	G	G	EG	G	EG	G	F	EG	NR	G	G	EG	NR
塑芯人造胶 Thermoplastic elastomer on plastic core	TEPB	4"-8"	70A°	140 ~ 280	-15	70	NR	NR	EG	EG		NR	NR	EG	G	G	NR	F	F	EG	G	NR	NR	EG	F	EG
塑芯人造胶 Thermoplastic elastomer on plastic core	TEPS	1"-5"	70A°	10 ~ 95	-15	70	NR	NR	EG	EG		NR	NR	EG	G	G	NR	F	F	EG	G	NR	NR	EG	F	EG
塑芯橡胶 Rubber on nylon core	RBNS	3"-5"	72A°	80 ~ 120	-30	60	EG	EG	EG	EG		EG	G	EG	G	G	F	F	F	EG	EG	NR	F	EG	F	G
塑芯橡胶 Rubber on nylon core	RBNB	4"-6"	72A°	100 ~ 280	-30	60	EG	EG	EG	EG		EG	G	EG	G	G	F	F	F	EG	EG	NR	F	EG	F	G
钢芯橡胶 Rubber on steel plate structure	RBSF	3"-8"	72A°	80 ~ 320	-30	60	EG	EG	EG	EG		EG	G	EG	G	G	F	F	F	EG	EG	NR	F	EG	F	G
铁芯橡胶 Rubber on cast iron core	RBCB	5"-8"	86A°	220 ~ 400	-30	60	EG	EG	EG	EG		EG	G	EG	G	G	F	F	F	EG	EG	NR	F	EG	F	G
充气轮 penuumatic tire on steel plate structure	NUSB	8"-10"	62A°	150 ~ 170	-30	50	F	EG	EG	EG		EG	G	G	G	G	NR	NR	NR	G	G	NR	NR	EG	F	G
发泡轮 Rubber on steel plate structure	RSSB	6"-10"	62A°	150 ~ 250	-10	50	F	F	EG	EG		EG	EG	G	G	G	NR	NR	F	F	EG	NR	NR	EG	F	G
铸铁轮 Cast iron	CICL CICB	3"-8"	> 100D	105 ~ 450	-70	400	F	NR	NR	NR		G	NR	G	NR	NR	G	NR	NR	NR	NR	EG	EG	NR	EG	F
酚醛轮 Phenolic aldehyde	PA-B	3"-8"	80D	100 ~ 430	-25	200	NR	F	F	F		G	G	G	G	NR	G	F	F	NR	NR	G	F	F	EG	G

等级 EG-非常好 G-好的 F-一般 NR-不提倡

Grade EG-Extremely good G-Good F-General NR-No recommend

i7 CUSTOMIZED PRODUCTS? NO PROBLEM.

定制脚轮？找我们就对了。

如果您需要的脚轮产品有特殊规格及应用，不必犹豫，申牌有足够的实力和从业经验，满足所有定制要求。

If you need casters with special specifications and application, do not hesitate to apply for SHENPAI with sufficient strength and experience to meet all the customization requirements.



定制案例 CUSTOM CASE

材料专家 MATERIAL EXPERT



高回弹PU
High resilience PU

高回弹PU
High resilience PU
进口材料
Imported materials
高承载 高弹 高耐磨
High load, high elasticity and high wear resistance
运行速度可达14-20km/h
The operating speed can reach 14-20km/h

结构专家 STRUCTURAL EXPERT



叉车平衡轮
Fork wheel

带减震功效，适合各种复杂路面
With shock absorption, suitable for all kinds of complicated roads
带调节功效，适应多种高度要求
With adjustment function, suitable for multiple height requirements
运行速度可达6km/h
The operating speed can reach 6km/h

功能专家 FUNCTIONAL EXPERT



高端减震轮
High-end shockproof caster

平衡减震功效
Balanced shock absorption
载重高达3T
Load up to 3T

客户展示 Customer display



微型轮系列 Micro Duty

- 10A微型 Micro Duty
- 10B微型(镀铬款)
Micro Duty(Chromed)



1"-3"


10-50 Kg

- 适用于橱柜、小型设备配套等行业
It is suitable for cabinets, small equipment and other industries.

10A 系列 SERIES 微型 Micro Duty

10A

安装尺寸 Installation Drawing



平底活动 刹车底板
Plate of Swivel Caster

平底固定底板
Plate of Rigid Caster

丝杆
Threaded Stem

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a×b	孔径 Φd
1"	25	38×33	30×24	4.2
1.25"	32	38×33	30×24	4.2
1.5"	38	46×39	36×28	5.2
2"	50	59×47	46×35	6.2
2.5"	63	70×58	55×42	8.3
3"	75	70×58	55×42	8.3

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a×b	孔径 Φd
1"	25	36×20	29×13	4.2
1.25"	32	36×20	29×13	4.2
1.5"	38	46×25	36×15	5.2
2"	50	58×40	45×25	6.2
2.5"	63	70×47	55×28	8.3
3"	75	70×47	55×28	8.3

尺寸 D	轮径 D	丝杆 m×h
1.5"	38	M8×15
2"	50	M10×15
2.5"	63	M12×25
3"	75	M12×25




1-3"
10-50 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重(kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	丝杆活动 Threaded stem swivel	装箱数 PCs/CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
	轮面硬度 Tire Hardness 耐磨程度 Wearable Level 静音效果 Silent running 地面保护 Floor-protection	硬 Very Hard 适中 Medium 一般 Medium 适中 Medium	75D ± 3 20 ± 10N	聚丙烯 polypropylene	无轴承 None	1"	10A02-1001	700	10A01-1001	700	-	-	-	-	-	-
						1.25"	10A05-1002	500	10A04-1002	500	-	-	-	-	-	-
						1.5"	10A09-1003	300	10A07-1003	300	10A08-1003	250	10A10-1003	300	10A11-1003	250
						2"	10A14-1004	150	10A12-1004	150	10A13-1004	100	10A15-1004	150	10A16-1004	100
						2.5"	10A19-1005	80	10A17-1005	80	10A18-1005	60	10A20-1005	80	10A21-1005	60
						3"	10A24-1006	60	10A22-1006	60	10A23-1006	50	10A25-1006	60	10A26-1006	50

外形尺寸 Overall Dimensions

尺寸 D	轮径 D	平底全高 H	丝杆全高 H	偏心距 F	旋转半径 r
1"	25	35	-	12	24.5
1.25"	32	42	-	14	30
1.5"	38	50	56	17	36
2"	50	65	68	23	48
2.5"	63	82	85	29	60.5
3"	75	92	95	29	66.5



产品特点 Product Features

- 镀锌支架 • Galvanied bracket
- 板材厚度 • Thickness of steel plate


尺寸 Wheel Size	底板厚度 Thickness of top plate	支架厚度 Thickness of bracket
1"-1.25"	1.5mm	1.2mm
1.5"	1.5mm	1.5mm
2"	2mm	2mm
2.5"-3"	2.5mm	2mm

定制产品 Customized product




10B 系列 SERIES 微型 Micro Duty

安装尺寸 Installation Drawing




平底活动 刹车底板
Plate of Swivel Caster

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a×b	孔径 Φd
1"	25	39×33	30×24	4.3
1.25"	32	39×33	30×24	4.3
1.5"	38	46×39.5	36×28	4.3
2"	50	46×39.5	36×28	5.2



平底固定底板
Plate of Rigid Caster

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a×b	孔径 Φd
1"	25	38×30	30×24	4.3
1.25"	32	39×33	30×24	4.3
1.5"	38	46×37.5	36×28	4.3
2"	50	46×38	36×28	5.2



丝杆
Threaded Stem

尺寸 D	轮径 D	丝杆 m×h
1"	25	M8×20
1.25"	32	M8×20
1.5"	38	M8×20
2"	50	M10×25




1-2"
10-28 Kg

产品图片 Product image	性能参数 Performance parameters				轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重(kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	丝杆活动 Threaded stem swivel	装箱数 PCs/CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
TEPS 	轮面硬度 Tire Hardness	●●●●● 软 Soft	85±3A 50±20N	人造胶 thermoplastic elastomer on plastic core	单滚珠 Single ball bearing	1"	13	10		10B02-1510	650	10B01-1510	650	10B03-1510	550	10B04-1510	650	10B05-1510	550
	耐磨程度 Wearable Level	■■■■■ 良好 Good				1.25"	13	15		10B07-1511	500	10B06-1511	500	10B08-1511	400	10B09-1511	500	10B10-1511	400
	静音效果 Silent running	■■■■■ 顶级 Excellent				1.5"	17	20		10B12-1512	250	10B11-1512	250	10B13-1512	200	10B14-1512	250	10B15-1512	200
	地面保护 Floor-protection	■■■■■ 顶级 Excellent				2"	17	25		10B17-1513	150	10B16-1513	150	10B18-1513	100	10B19-1513	150	10B20-1513	100
NL-N 	轮面硬度 Tire Hardness	●●●●● 硬 Very Hard	75D±3 20±10N	尼龙 Nylon	无轴承 None	1"	13	15		10B02-1514	650	10B01-1514	650	10B03-1514	550	10B04-1514	650	10B05-1514	550
	耐磨程度 Wearable Level	■■■■■ 优秀 Very Good				1.25"	13	18		10B07-1515	500	10B06-1515	500	10B08-1515	400	10B09-1515	500	10B10-1515	400
	静音效果 Silent running	■■■■■ 一般 Medium				1.5"	17	25		10B12-1516	250	10B11-1516	250	10B13-1516	200	10B14-1516	250	10B15-1516	200
	地面保护 Floor-protection	■■■■■ 一般 Medium				2"	17	28		10B17-1517	150	10B16-1517	150	10B18-1517	100	10B19-1517	150	10B20-1517	100

外形尺寸 Overall Dimensions

尺寸 D	轮径 D	平底全高 H	丝杆全高 H	偏心距 F	旋转半径 r	旋转半径 R
1"	25	37.5	39.5	15.5	28	47.5
1.25"	32	44.5	46.5	15	31	49
1.5"	38	52	54	18.5	37.5	59.5
2"	50	64	67	19	44	62.5



产品特点 Product Features

- 镀铬支架 • Chromed bracket
- 优质TPR注塑而成 • Injection with TPR
- 保护地面，不留痕迹 • Floor-protective, traceless

• 板材厚度 • Thickness of steel plate

尺寸 Wheel Size	底板厚度 Thickness of top plate	支架厚度 Thickness of bracket
1-1.25"	1.2mm	1.2mm
1.5-2"	1.5mm	1.5mm

轻型轮系列 Light Duty

- 15A轻型 (2"-2.5") Light Duty
- 20C轻型 (3"-4") Light Duty



2"-4"


35-90 Kg

- 适用于纺织厂、美容、医疗、机械制造等多种行业


It is suitable for textile industry, beauty treatment, medical treatment, machinery manufacturing, and many other industries.

15A 系列 SERIES 轻型 Light Duty


安装尺寸 Installation Drawing



平底活动 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem




2-2.5"
35-40 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	丝杆活动 Threaded stem swivel	装箱数 PCs/CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
PUPA 	轮面硬度 Tire Hardness: 适中 Medium 耐磨程度 Wearable Level: 顶级 Excellent 静音效果 Silent running: 优秀 Very Good 地面保护 Floor-protection: 优秀 Very Good	塑芯聚氨酯 Polyurethane on plastic core	一体轴承 Annular Ball Bearing	2"	25	35	15A03-1010	100	15A01-1010	100	15A02-1010	80	15A04-1010	100	15A05-1010	80
				2.5"	25	40	15A08-1011	80	15A06-1011	80	15A07-1011	70	15A09-1011	80	15A10-1011	70
NLPA 	轮面硬度 Tire Hardness: 硬 Very Hard 耐磨程度 Wearable Level: 优秀 Very Good 静音效果 Silent running: 一般 Medium 地面保护 Floor-protection: 一般 Medium	塑芯尼龙 Nylon on plastic core	一体轴承 Annular Ball Bearing	2"	25	35	15A03-1007	100	15A01-1007	100	15A02-1007	80	15A04-1007	100	15A05-1007	80
				2.5"	25	40	15A08-1008	80	15A06-1008	80	15A07-1008	70	15A09-1008	80	15A10-1008	70

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
2"	53	72	77	26	52.5	81.5
2.5"	63	85	90	28	59.5	82




产品特点 Product Features


- 镀锌支架
- 底板厚度2mm
- 支架厚度2mm
- 防缠绕设计
- 适用于纺织行业
- Galvanied bracket
- Thickness of top plate 2mm
- Thickness of bracket 2mm
- Thread proof design
- Suitable for textile industry

20C 系列 SERIES 轻型 Light Duty


安装尺寸 Installation Drawing




平底活动 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem



插杆
Stem of Swivel Caster




3-5"

70-90 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN	插杆活动 Grip Ring stem swivel	装箱数 PCs /CTN	插杆刹车 Grip Ring stem swivel with brake	装箱数 PCs /CTN
TEPS 	轮面硬度 Tire Hardness: 较软 Soft 耐磨程度 Wearable Level: 良好 Good 静音效果 Silent running: 顶级 Excellent 地面保护 Floor-protection: 顶级 Excellent	人造胶 Thermoplastic elastomer on plastic core	单滚珠 Single ball bearing	3"	25	70	20C21-1397	35	20C19-1397	35	20C20-1397	30	20C28-1397	35	20C29-1397	30	20C42-1397	35	20C43-1397	30
				4"	25	80	20C27-1399	30	20C25-1399	30	20C26-1399	25	20C32-1399	30	20C33-1399	25	20C44-1399	30	20C45-1399	25
PUPS 	轮面硬度 Tire Hardness: 适中 Medium 耐磨程度 Wearable Level: 顶级 Excellent 静音效果 Silent running: 优秀 Very Good 地面保护 Floor-protection: 优秀 Very Good	聚氨酯 Polyurethane on plastic core	单滚珠 Single ball bearing	3"	25	80	20C21-1621	35	20C19-1621	35	20C20-1621	30	20C28-1621	35	20C29-1621	30	20C42-1621	35	20C43-1621	30
				4"	25	90	20C27-1622	30	20C25-1622	30	20C26-1622	25	20C32-1622	30	20C33-1622	25	20C44-1622	30	20C45-1622	25

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
3"	75	105	108	36	73.5	102
4"	100	130	133	34	84	102



产品特点 Product Features

- 喷塑银灰支架
- 底板2.5mm
- 支架2mm
- 有效保护地面
- 产品美观
- 使用轻便
- Powder-coated bracket
- Thickness of top plate 2.5mm
- Thickness of bracket 2mm
- Floor protective
- Elegant appearance
- Easy to brake



3"-4"

80-160 Kg

● 适用于电子、纺织、机械设备、医疗等行业，使用范围广


It can be widely used in electronics, textile, machinery, medical and other industries.

融合标准




20A 系列 SERIES 中型 Medium Duty


安装尺寸 Installation Drawing



平底活动/刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem




3-5"
105-145 Kg

产品图片 Product image	性能参数 Performance parameters				轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	丝杆活动 Threaded stem swivel	装箱数 PCs/CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
PUPA 	轮面硬度 Tire Hardness	●●●●● 适中 Medium	95 ± 3A°	聚氨酯 Polyurethane on plastic core	一体轴承 Annular Ball Bearing	3"	30	105		20AB1-1014	35	20A01-1014	35	20A02-1014	30	20A04-1014	35	20A05-1014	30
	耐磨程度 Wearable Level	■■■■■ 顶级 Excellent	60 ± 10N			3.5"	32	115		20AB2-1015	35	20A10-1015	35	20A11-1015	30	20A13-1015	35	20A14-1015	30
	静音效果 Silent running	■■■■■ 优秀 Very Good				4"	32	135		20AB3-1016	30	20A19-1016	30	20A20-1016	25	20A22-1016	30	20A23-1016	25
	地面保护 Floor-protection	■■■■■ 优秀 Very Good				5"	32	145		20AB4-1017	20	20A28-1017	20	20A29-1017	15	20A31-1017	20	20A32-1017	15
NLPA 	轮面硬度 Tire Hardness	●●●●● 硬 Very Hard	75D ± 3	尼龙 Nylon on plastic core	一体轴承 Annular Ball Bearing	3"	30	105		20AB1-1018	35	20A01-1018	35	20A02-1018	30	20A04-1018	35	20A05-1018	30
	耐磨程度 Wearable Level	■■■■■ 优秀 Very Good	60 ± 20N			3.5"	32	115		20AB2-1019	35	20A10-1019	35	20A11-1019	30	20A13-1019	35	20A14-1019	30
	静音效果 Silent running	■■■■■ 一般 Medium				4"	32	135		20AB3-1020	30	20A19-1020	30	20A20-1020	25	20A22-1020	30	20A23-1020	25
	地面保护 Floor-protection	■■■■■ 一般 Medium				5"	32	145		20AB4-1021	20	20A28-1021	20	20A29-1021	15	20A31-1021	20	20A32-1021	15
PP-B 	轮面硬度 Tire Hardness	●●●●● 硬 Very Hard	75D ± 3	聚丙烯 Polypropylene	双滚珠 Ball bearing	3"	30	105		20AB1-1040	35	20A01-1040	35	20A02-1040	30	20A04-1040	35	20A05-1040	30
	耐磨程度 Wearable Level	■■■■■ 适中 Medium	50 ± 10N			3.5"	32	115		20AB2-1041	35	20A10-1041	35	20A11-1041	30	20A13-1041	35	20A14-1041	30
	静音效果 Silent running	■■■■■ 一般 Medium				4"	32	135		20AB3-1042	30	20A19-1042	30	20A20-1042	25	20A22-1042	30	20A23-1042	25
	地面保护 Floor-protection	■■■■■ 适中 Medium				5"	32	145		20AB4-1043	20	20A28-1043	20	20A29-1043	15	20A31-1043	20	20A32-1043	15

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
3"	75	108	111	34	71.5	110.5
3.5"	88	120	123	32	76	110.5
4"	100	135	138	32	82	110.5
5"	125	160	163	32	94.5	112.5



产品特点 Product Features


- 镀锌支架
Classic metal brake
- 底板厚度3.5~4mm
- 支架厚度2.5~4mm
- Galvanied bracket
- Thickness of top plate 3.5~4mm
- Thickness of bracket 2.5~4mm

选配支架 Optional Brackets

款式 Brake	轻便金属刹 Classic metal brake	轻便尼龙刹 Easy-pedal brake	长尾刹 Longtail brake
3"	20A87	20AB5	20A61
4"	20A88	20AB6	20A67
5"	20A89	20AB7	20A70
特点 Feature	制动轻便 Very easy to operate	制动轻便 Very easy to operate	制动轻 有效保护轮面 Tire protective

20A 系列 中型 Medium Duty


安装尺寸
Installation Drawing



产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	丝杆活动 Threaded stem swivel	装箱数 PCs/CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
PUPA 	轮面硬度 Tire Hardness 耐磨程度 Wearable Level 静音效果 Silent running 地面保护 Floor-protection	较软 Soft 良好 Good 良好 Good 良好 Good	95 ± 3A° 60 ± 20N 橡塑 Polyurethane on plastic core 一体轴承 Annular ball bearing	3"	30	105	20AB1-1022	35	20A01-1022	35	20A02-1022	30	20A04-1022	35	20A05-1022	30
				3.5"	32	115	20AB2-1023	35	20A10-1023	35	20A11-1023	30	20A13-1023	35	20A14-1023	30
				4"	32	135	20AB3-1024	30	20A19-1024	30	20A20-1024	25	20A22-1024	30	20A23-1024	25
				5"	32	145	20AB4-1025	20	20A28-1025	20	20A29-1025	15	20A31-1025	20	20A32-1025	15
PUPA 	轮面硬度 Tire Hardness 耐磨程度 Wearable Level 静音效果 Silent running 地面保护 Floor-protection	较软 Soft 良好 Good 良好 Good 良好 Good	95 ± 3A° 60 ± 20N 橡塑 Polyurethane on plastic core 一体轴承 Annular ball bearing	3"	30	105	20AB1-1026	35	20A01-1026	35	20A02-1026	30	20A04-1026	35	20A05-1026	30
				3.5"	32	115	20AB2-1027	35	20A10-1027	35	20A11-1027	30	20A13-1027	35	20A14-1027	30
				4"	32	135	20AB3-1028	30	20A19-1028	30	20A20-1028	25	20A22-1028	30	20A23-1028	25
				5"	32	145	20AB4-1029	20	20A28-1029	20	20A29-1029	15	20A31-1029	20	20A32-1029	15
PUPS 	轮面硬度 Tire Hardness 耐磨程度 Wearable Level 静音效果 Silent running 地面保护 Floor-protection	适中 Medium 顶级 Excellent 优秀 Very Good 优秀 Very Good	95 ± 3A° 60 ± 10N 超级聚氨酯 Polyurethane on plastic core 单滚珠 Single ball bearing	3"	32	100	20AB1-1354	35	20A01-1354	35	20A02-1354	30	20A04-1354	35	20A05-1354	30
				4"	32	130	20AB3-1355	30	20A19-1355	30	20A20-1355	25	20A22-1355	30	20A23-1355	25
				5"	32	140	20AB4-1356	20	20A29-1356	20	20A29-1356	15	20A31-1356	20	20A32-1356	15
PUPB 	轮面硬度 Tire Hardness 耐磨程度 Wearable Level 静音效果 Silent running 地面保护 Floor-protection	适中 Medium 顶级 Excellent 优秀 Very Good 优秀 Very Good	95 ± 3A° 60 ± 10N 超级聚氨酯 Polyurethane on plastic core 双滚珠 Ball bearing	3"	32	110	20AB1-0370	35	20A01-0370	35	20A02-0370	30	20A04-0370	35	20A05-0370	30
				4"	32	140	20AB3-0371	30	20A19-0371	30	20A20-0371	25	20A22-0371	30	20A23-0371	25
				5"	32	150	20AB4-0372	20	20A28-0372	20	20A29-0372	15	20A31-0372	20	20A32-0372	15

外形尺寸
Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
3"	75	108	111	34	71.5	110.5
3.5"	88	120	123	32	76	110.5
4"	100	135	138	32	82	110.5
5"	125	160	163	32	94.5	112.5



产品特点
Product Features


- 镀锌支架
Classic metal brake
- 底板厚度3.5~4mm
- 支架厚度2.5~4mm
- Galvanied bracket
- Thickness of top plate 3.5~4mm
- Thickness of bracket 2.5~4mm

选配支架
Optional Brackets


款式 Brake	轻便金属刹 Classic metal brake	轻便尼龙刹 Easy-pedal brake	长尾刹 Longtail brake
3"	20A87	20AB5	20A61
4"	20A88	20AB6	20A67
5"	20A89	20AB7	20A70
特点 Feature	制动轻便 Very easy to operate	制动轻便 Very easy to operate	制动轻 有效保护轮面 Tire protective

20A 系列 SERIES 中型 Medium Duty


安装尺寸 Installation Drawing



平底活动/ 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem




3-5"
105-145 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	丝杆活动 Threaded stem swivel	装箱数 PCs/CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
TEPS 	轮面硬度 Tire Hardness	人造胶 Thermoplastic elastomer on plastic core	单滚珠 Single ball bearing	3"	32	85	20AB1-1375	35	20A01-1375	35	20A87-1375	30	20A04-1375	35	20AA5-1375	30
	耐磨程度 Wearable Level			4"	32	100	20AB3-1377	30	20A19-1377	30	20A88-1377	25	20A22-1377	30	20AA6-1377	25
	静音效果 Silent running			5"	32	110	20AB4-1378	20	20A28-1378	20	20A89-1378	15	20A31-1378	20	20AA7-1378	15
TEPS 	地面保护 Floor-protection	人造胶 Thermoplastic elastomer on plastic core	单滚珠 Single ball bearing	3"	32	70	20AB1-1593	35	20A01-1593	35	20A87-1593	30	20A04-1593	35	20AA5-1593	30
	轮面硬度 Tire Hardness			4"	32	80	20AB3-1594	30	20A19-1594	30	20A88-1594	25	20A22-1594	30	20AA6-1594	25
	耐磨程度 Wearable Level			5"	32	90	20AB4-1595	20	20A28-1595	20	20A89-1595	15	20A31-1595	20	20AA7-1595	15
RBNS 	静音效果 Silent running	橡胶 Rubber on nylon core	单滚珠 Single ball bearing	3"	32	80	20AB1-1538	35	20A01-1538	35	20A87-1538	30	20A04-1538	35	20AA5-1538	30
	地面保护 Floor-protection			4"	32	100	20AB3-1539	30	20A19-1539	30	20A88-1539	25	20A22-1539	30	20AA6-1539	25
	轮面硬度 Tire Hardness			5"	32	120	20AB4-1540	20	20A28-1540	20	20A89-1540	15	20A31-1540	20	20AA7-1540	15
RBNS 	耐磨程度 Wearable Level	橡胶 Rubber on nylon core	单滚珠 Single ball bearing	3"	32	80	20AB1-1044	35	20A01-1044	35	20A87-1044	30	20A04-1044	35	20AA5-1044	30
	静音效果 Silent running			4"	32	100	20AB3-1045	30	20A19-1045	30	20A88-1045	25	20A22-1045	30	20AA6-1045	25
	地面保护 Floor-protection			5"	32	120	20AB4-1046	20	20A28-1046	20	20A89-1046	15	20A31-1046	20	20AA7-1046	15

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
3"	75	108	111	34	71.5	108.5
4"	100	135	138	32	82	108.5
5"	125	160	163	32	94.5	112.5



产品特点 Product Features


- 镀锌支架
• 底板厚度3.5~4mm
• 支架厚度2.5~4mm
• 防缠绕设计
• Galvanied bracket
• Thickness of top plate 3.5~4mm
• Thickness of bracket 2.5~4mm
• Thread proof design

选配支架 Optional Brackets


款式 Brake	经典款金属刹 Classic metal brake	轻便尼龙刹 Easy-pedal brake	长尾刹 Longtail brake
3"	20A02	20AB5	20A61
4"	20A20	20AB6	20A67
5"	20A29	20AB7	20A70
特点 Feature	锁紧力大, 10000次寿命测试 Tough brake, 10000 times life	制动轻便 Very easy to operate	制动轻 有效保护轮面 Tire protective

20A 系列 SERIES 中型 Medium Duty

安装尺寸 Installation Drawing



平底活动/ 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster




3-5"
100-160 Kg

 产品图片 Product image	 性能参数 Performance parameters			 轮面材质 Wheel Material	 轮片轴承 Bearing	 轮片直径 (inch) Wheel Diameter	 轮面宽度 (mm) Tire width	 载重 (kg) Capacity	 平底固定 Rigid	 装箱数 PCs/CTN	 平底活动 Swivel	 装箱数 PCs/CTN	 平底刹车 Swivel with brake	 装箱数 PCs/CTN
CICL 	轮面硬度 Tire Hardness	硬 Very Hard	> 100D	铸铁 Cast iron	轴承 Sleeve	3"	30	110	20AB1-1037	35	20A84-1037	35	-	-
	耐磨程度 Wearable Level	优秀 Very Good	50 ± 20N			4"	32	150	20AB3-1038	30	20A85-1038	30	-	-
	静音效果 Silent running	较差 Poor				5"	32	160	20AB4-1039	20	20A86-1039	20	-	-
	地面保护 Floor-protection	较差 Poor												
PA-B 	轮面硬度 Tire Hardness	硬 Very Hard	80D ± 3	酚醛 Phenolic aldehyde	双滚珠 Ball bearing	3"	32	100	20AB1-1663	35	20A84-1663	35	20A87-1663	30
	耐磨程度 Wearable Level	优秀 Very Good	50 ± 20N			4"	32	130	20AB3-1664	30	20A85-1664	30	20A88-1664	25
	耐温性能 High-Temp Endurance	优秀 Very Good	-25℃ - +200℃			5"	32	145	20AB4-1665	20	20A86-1665	20	20A89-1665	15
	地面保护 Floor-protection	一般 Medium												
NH-B 	轮面硬度 Tire Hardness	硬 Very Hard	75D ± 3	高温尼龙 High temperature nylon	双滚珠 Ball bearing	3"	32	100	20AB1-1666	35	20A84-1666	35	20A87-1666	30
	耐磨程度 Wearable Level	优秀 Very Good	50 ± 20N			4"	32	130	20AB3-1667	30	20A85-1667	30	20A88-1667	25
	耐温性能 High-Temp Endurance	顶级 Excellent	-25℃ - +200℃			5"	32	145	20AB4-1668	20	20A86-1668	20	20A89-1668	15
	地面保护 Floor-protection	一般 Medium												

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
3"	75	108	34	71.5	108.5
4"	100	135	32	82	108.5
5"	125	160	32	94.5	112.5



产品特点 Product Features

- 镀锌支架 • Galvanied bracket
- 底板厚度3.5mm • Thickness of top plate 3.5mm
- 支架厚度2.5mm • Thickness of bracket 2.5mm





申牌万向轮
SHENPAI Caster
—SINCE 1993—

中重型轮系列 Medium-heavy Duty

- 25A 中重型(中空铆接款)
Med-heavy Duty (Kingpinless)
- 25X 中重型(经济配套款)
Med-heavy Duty (Economical)
- 25D 中重型(折叠急救病床用)
Foldable Ambulance Bed



3"-8"

80-550 Kg

- 适用于仓储物流、汽车工业、机械制造、医疗等行业

It is suitable for warehousing, logistics, automotive industry, machinery manufacturing, medical and other industries.


融合标准



25A 系列 SERIES

中重型(中空铆接款) Med-heavy Duty (Kingpinless)

安装尺寸 Installation Drawing



尺寸 D	轮径 D	底板尺寸 A x B	孔距 a1 x b1	孔距 a2 x b2	孔径 Φd
4"	100	97 x 97	74 x 74	67 x 67	11
5"	130	110 x 110	90 x 90	75 x 75	11
6"	150	120 x 120	90 x 90	75 x 75	11
8"	200	140 x 140	115 x 115	100 x 100	12

尺寸 D	轮径 D	底板尺寸 A x B	孔距 a1 x b1	孔距 a2 x b2	孔径 Φd
4"	100	120 x 82	90 x 50	80 x 45	11
5"	130	138 x 90	112 x 56	100 x 53	11
6"	150	138 x 90	112 x 56	100 x 53	11
8"	200	152 x 103	119 x 63	112 x 56	12

丝杆
Threaded Stem




3-8"
80-550 Kg

产品图片 Product image	性能参数 Performance parameters			轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底固定刹车 Rigid with brake	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN
	轮面硬度 Tire Hardness	软 Very Soft	75 ± 3A 130 ± 70N	钢芯橡胶 Rubber on steel plate structure	法兰轴承 Flanged ball bearing	3"	32	80	25A03-1062	40	25A04-1062	40	25A01-1062	40	25A02-1062	40	-	-	-	-
	耐磨程度 Wearable Level	适中 Medium				4"	38	130	25A12-1063	20	25A13-1063	18	25A10-1063	20	25A11-1063	18	25A14-1063	20	25A15-1063	18
	静音效果 Silent running	顶级 Excellent				5"	40	200	25A21-1064	12	25A22-1064	10	25A19-1064	12	25A20-1064	10	25A23-1064	12	25A24-1064	10
	地面保护 Floor-protection	顶级 Excellent				6"	43	250	25A30-1065	8	25A31-1065	8	25A28-1065	8	25A29-1065	8	25A32-1065	8	25A33-1065	8
									8"	45	320	25A39-1066	5	25A40-1066	4	25A37-1066	5	25A38-1066	4	-
	轮面硬度 Tire Hardness	适中 Medium	95 ± 3A° 120 ± 20N	钢芯聚氨酯 Polyurethane on steel plate structure	法兰轴承 Flanged ball bearing	3"	32	120	25A03-1052	40	25A04-1052	40	25A01-1052	40	25A02-1052	40	-	-	-	-
	耐磨程度 Wearable Level	优秀 Very Good				4"	32	230	25A12-1053	20	25A13-1053	18	25A10-1053	20	25A11-1053	18	25A14-1053	20	25A15-1053	18
	静音效果 Silent running	优秀 Very Good				5"	35	280	25A21-1054	12	25A22-1054	10	25A19-1054	12	25A20-1054	10	25A23-1054	12	25A24-1054	10
	地面保护 Floor-protection	顶级 Excellent				6"	38	380	25A30-1055	8	25A31-1055	8	25A28-1055	8	25A29-1055	8	25A32-1055	8	25A33-1055	8
									8"	42	450	25A39-1056	5	25A40-1056	4	25A37-1056	5	25A38-1056	4	-
	轮面硬度 Tire Hardness	硬 Very Hard	75D ± 3 110 ± 50N	钢芯尼龙 Nylon on steel plate structure	法兰轴承 Flanged ball bearing	3"	32	150	25A03-1057	40	25A04-1057	40	25A01-1057	40	25A02-1057	40	-	-	-	-
	耐磨程度 Wearable Level	顶级 Excellent				4"	32	280	25A12-1058	20	25A13-1058	18	25A10-1058	20	25A11-1058	18	25A14-1058	20	25A15-1058	18
	静音效果 Silent running	一般 Medium				5"	35	350	25A21-1059	12	25A22-1059	10	25A19-1059	12	25A20-1059	10	25A23-1059	12	25A24-1059	10
	地面保护 Floor-protection	优秀 Very Good				6"	38	450	25A30-1060	8	25A31-1060	8	25A28-1060	8	25A29-1060	8	25A32-1060	8	25A33-1060	8
									8"	42	550	25A39-1061	5	25A40-1061	4	25A37-1061	5	25A38-1061	4	-

外形尺寸 Overall Dimensions

尺寸 D	轮径 D	平底全高 H	丝杆全高 H	偏心距 F	旋转半径 r
3"	75	100	-	23.5	61
4"	100	144	144	35	85
5"	130	172	172	38	103
6"	150	197	197	40	115
8"	200	250	-	58	158



产品特点 Product Features

- 镀锌支架 Galvanied bracket
- 中空式设计 hollow bracket design
- 抗冲击 Shock proof
- 转动轻便 Easy to twirl
- 日式JIS标准 JIS standard

板材厚度 Thickness of steel plate

尺寸 Wheel Size	底板厚度 Thickness of top plate	支架厚度 Thickness of bracket
3"	2.5mm	2.5mm
4"-6"	4mm	3mm
8"	4mm	4mm


选配轮片 Optional Wheels




25X 系列 SERIES

中重型(经济配套款) Med-heavy Duty (Economical)


安装尺寸 Installation Drawing



平底活动/ 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a1×b1	孔距 a2×b2	孔径 Φd
4"	100	97×97	74×74	67×67	11
5"	130	110×110	90×90	75×75	11
6"	150	120×120	90×90	75×75	11

尺寸 D	轮径 D	底板尺寸 A×B	孔距 a1×b1	孔距 a2×b2	孔径 Φd
4"	100	120×82	90×50	80×45	11
5"	130	120×82	90×50	80×45	11
6"	150	138×90	112×56	100×53	11




5-6"
100-230 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底固定刹车 Rigid with brake	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN
PUPF 	轮面硬度 Tire Hardness 耐磨程度 Wearable Level 静音效果 Silent running 地面保护 Floor-protection	适中 Medium 优秀 Very Good 优秀 Very Good 顶级 Excellent	95±3A° 110±70N	聚氨酯 Polyurethane on plastic core	法兰轴承 Flanged ball bearing	4" 32 100 5" 35 150 6" 38 230	25X03-1078	20	25X04-1078	18	25X01-1078	20	25X02-1078	18	-	-	-	-
							25X12-1079	12	25X13-1079	10	25X10-1079	12	25X11-1079	10	25XA4-1079	12	25XA5-1079	10
							25X21-1080	8	25X22-1080	8	25X19-1080	8	25X20-1080	8	25XA0-1080	8	25XA1-1080	8

外形尺寸 Overall Dimensions

尺寸 D	轮径 D	平底 全高 H	丝杆 全高 H	偏心距 F	旋转 半径 r
4"	100	144	-	35	85
5"	130	172	172	38	103
6"	150	197	197	40	115




产品特点 Product Features

- 镀锌支架
- 底板4mm
- 支架3mm
- Galvanied bracket
- Thickness of top plate 4mm
- Thickness of bracket 3mm

25D 系列 SERIES 中重型(折叠急救病床用) Foldable Ambulance Bed


安装尺寸 Installation Drawing



产品图片 Product image	性能参数 Performance parameters		轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	插杆固定 Stem of Rigid Caster	装箱数 PCs /CTN	插杆活动 Stem of Swivel Caster	装箱数 PCs /CTN	插杆刹车 Stem swivel with brake	装箱数 PCs /CTN
RBNB 	轮面硬度 Tire Hardness	●●●●● 软 Very Soft	橡胶 Rubber on nylon core	双滚珠 Ball bearing	5"	38	120	25D03-1317	14	25D01-1317	14	25D02-1317	14
	耐磨程度 Wearable Level	■●●●● 适中 Medium			6"	38	140	25D06-1318	14	25D04-1318	14	25D05-1318	14
PUPB 	静音效果 Silent running	■●●●● 顶级 Excellent	聚氨酯 Polyurethane on plastic core	双滚珠 Ball bearing	5"	38	130	25D03-1373	14	25D01-1373	14	25D02-1373	14
	地面保护 Floor-protection	■●●●● 顶级 Excellent			6"	38	150	25D06-1374	14	25D04-1374	14	25D05-1374	14

外形尺寸 Overall Dimensions

尺寸	轮径	插杆全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
5"	125	168	35	97.5	126
6"	150	195	35	110	126



产品特点 Product Features

- 适用于折叠病床
- 脚轮横置后立即停止晃动
- 静音减震
- 喷塑支架
- 支架2.5mm
- 可选配 $\phi 30$ 插杆
- Suitable for foldable hospital bed
- Anti-waggle design while caster is put down
- Silent running
- Powder bracket
- Thickness of bracket 2.5mm
- Optional stem: $\phi 30$



申牌万向轮
SHENPAI Caster
—SINCE 1993—

低重心型轮系列 Low-barycenter Duty

- 30A低重心型(轻载)
Low-barycenter(Light duty)
- 30B低重心型(中载)
Low-barycenter(Medium duty)
- 32A调节轮(重载)
Leveling Casters(Heavy Duty)




1.5"-4"

150-1000 Kg


- 适用于机械设备、仓储物流等行业
It is suitable for machinery, warehousing, logistics and other industries.

30A 系列 SERIES 低重心型(轻载) Low-barycenter(Light duty)


安装尺寸 Installation Drawing



平底活动 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem




2.5-3"
150-500 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN
I 款 NL-N	轮面硬度 Tire Hardness	联体尼龙 Nylon	滚针 Needle bearing	2.5"	46	150	30A03-1087	30	30A01-1087	30	30A02-1087	24	30A04-1087	30	30A05-1087	24
	耐磨程度 Wearable Level			3"	46	200	30A08-1088	25	30A06-1088	25	30A07-1088	24	30A09-1088	25	30A10-1088	24
II 款 NL-B	轮面硬度 Tire Hardness	改性尼龙 (新) Nylon (new)	双滚珠 Ball bearing	2.5"	46	450	30A03-1314	30	30A22-1314	30	30A23-1314	22	30A24-1314	30	30A25-1314	22
	耐磨程度 Wearable Level			3"	46	500	30A08-1315	25	30A26-1315	25	30A27-1315	22	30A28-1315	25	30A29-1315	22

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
I 款	D	D	H	H	F	r
2.5"	65	90	97	24	56.5	96
3"	75	100	108	25	62.5	96

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
II 款	D	D	H	H	F	r
2.5"	65	90	97	30	62.5	95
3"	75	100	108	30	67.5	95



产品特点 Product Features




- 电泳支架 • Electrophoretic coating
- 产品高度低 • Low-barycenter design
- 承载大 • High capacity
- 材料耐磨 • Wearable wheel material

- I 款 • 2.5"底板3mm 支架3mm
• 3"底板4mm 支架4mm
- II 款 • 底板4mm 支架4mm
- 2.5 "Thickness of top plate 3mm, Thickness of bracket 3mm
- 3 "Thickness of top plate 4mm, Thickness of bracket 4mm
- Thickness of top plate 4mm
- Thickness of bracket 4mm

30B 系列 SERIES 低重心型(中载) Low-barycenter(Medium duty)


安装尺寸 Installation Drawing

2.5-3"




丝杆
Threaded Stem

4"



平底活动 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster




2.5-4"
150-400 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN
NLAA 	轮面硬度 Tire Hardness	●●●●● 硬 Very Hard	75D ± 3	铝芯尼龙 Nylon	一体轴承 Annular Ball Bearing	2.5"	30B03-1089	30	30B01-1089	30	30B02-1089	24	30B04-1089	30	30B05-1089	24
	推动省力 Starting Thrust					3"	30B08-1090	25	30B06-1090	25	30B07-1090	24	30B09-1090	25	30B10-1090	24
	静音效果 Silent running					4"	30B18-1092	12	30B16-1092	12	30B17-1092	10	30B19-1092	12	30B20-1092	10
	耐磨程度 Wearable Level															
PUAA 	轮面硬度 Tire Hardness	●●●●● 适中 Medium	95 ± 3A°	聚氨酯 Polyurethane on plastic core	一体轴承 Annular Ball Bearing	2.5"	30B03-1094	30	30B01-1094	30	30B02-1094	24	30B04-1094	30	30B05-1094	24
	推动省力 Starting Thrust					3"	30B08-1095	25	30B06-1095	25	30B07-1095	24	30B09-1095	25	30B10-1095	24
	静音效果 Silent running					4"	30B18-1097	12	30B16-1097	12	30B17-1097	10	30B19-1097	12	30B20-1097	10
	耐磨程度 Wearable Level															

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
2.5"	65	90	97	30	62.5	78
3"	75	108	116	30	67.5	78
4"	100	148	148	40	90	90




产品特点 Product Features

- 电泳支架
- 底板4mm
- 支架4mm
- 铝芯骨架
- Electrophoretic coating
- Thickness of top plate 4mm
- Thickness of bracket 4mm
- Aluminium core


32A 系列 SERIES 调节轮 (重载) Leveling Casters (Heavy Duty)

安装尺寸 Installation Drawing

尺寸 D	轮径 D	底板尺寸 A x B	安装孔距 a x b	孔径 Φd	孔顶 Φd
1.5	40	55 x 55	42 x 42	7	M8
2	50	74.5 x 74.5	57 x 57	7.5	M12
2.5	62	90 x 90	70 x 70	8.8	M14
3	75	94.5 x 94.5	70 x 70	11	M14
3	75	94.5 x 94.5	70 x 70	11	M14



平底活动 刹车底板
Plate of Swivel Caster



顶孔
Hole Top





2.5-4"
150-400 Kg

产品图片 Product image	性能参数 Performance parameters			轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底活动 Swivel	装箱数 PCs /CTN	顶孔活动	装箱数 PCs /CTN
NL-N 	轮面硬度 Tire Hardness	●●●●● 硬 Very Hard	75D ± 3	尼龙 Nylon	无轴承 None	1.5"	19	50	32A01-1611	40	32A07-1611	40
	推动省力 Starting Thrust	■■■■■ 顶级 Excellent	100 ± 40N			2"	24	250	32A02-1612	24	32A08-1612	24
	静音效果 Silent running	■■■■■ 一般 Medium				2.5"	30	500	32A03-1613	12	32A09-1613	12
	耐磨程度 Wearable Level	■■■■■ 优秀 Very Good				3"	31	750	32A04-1614	12	32A10-1614	12
						3"	31	1000	32A05-1614	12	32A11-1614	12

外形尺寸 Overall Dimensions

尺寸 D	轮径 D	平底 全高 H	偏心距 F	旋转 半径 r
1.5"	40	72	30.5	50.5
2"	50	86	38	63
2.5"	62	106.5	44	75
3"	75	120	52.5	90
3"	75	120	52.5	90



产品特点 Product Features

- 适用于仪器设备
- 调节旋钮用于固定脚轮
- 改性注塑尼龙
- 高承载
- Suitable for devices
- Rotary knob to settle caster
- Modified nylon
- High capacity



申牌万向轮
SHENPAI Caster
—SINCE 1993—

重型轮系列 Heavy Duty

- 35A重型 (淬火底板)
Heavy Duty(Quenched ball track)
- 35C重型 (经济型)
Heavy Duty(Economical)



4"-8"

200-500 Kg

- 适用于工厂搬运、仓储物流、机械制造等多种行业

It is suitable for various industries such as plant handling, storage and logistics, machinery manufacturing, and so on.


融合标准



35A 系列 SERIES

重型 (淬火底板) Heavy Duty (Quenched Ball Track)

安装尺寸 Installation Drawing



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"

280-460 Kg

产品图片 Product image	性能参数 Performance parameters			轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
	轮面硬度 Tire Hardness	适中 Medium	95 ± 3A°	超级聚氨酯 Polyurethane on plastic core	双滚珠 Ball bearing	4"	45	280	35A62-1814	15	35A60-1814	15	35A61-1814	10
	推动省力 Starting Thrust	优秀 Very Good	110 ± 20N			5"	48	320	35A65-1815	12	35A63-1815	12	35A64-1815	8
	静音效果 Silent running	优秀 Very Good	6"			50	400	35A68-1816	8	35A66-1816	8	35A67-1816	7	
	耐磨程度 Wearable Level	顶级 Excellent	8"			50	430	35A71-1818	5	35A69-1818	5	35A70-1818	5	
	轮面硬度 Tire Hardness	适中 Medium	95 ± 3A°	超级聚氨酯 Polyurethane on plastic core	双滚珠 Ball bearing	4"	45	300	35A62-1325	15	35A60-1325	15	35A61-1325	10
	推动省力 Starting Thrust	优秀 Very Good	110 ± 30N			5"	48	380	35A65-1326	12	35A63-1326	12	35A64-1326	8
	静音效果 Silent running	优秀 Very Good	6"			50	450	35A68-1327	8	35A66-1327	8	35A67-1327	7	
	耐磨程度 Wearable Level	顶级 Excellent	8"			50	460	35A71-1328	5	35A69-1328	5	35A70-1328	5	
	轮面硬度 Tire Hardness	适中 Medium	95 ± 3A°	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	4"	46	300	35A62-1128	12	35A60-1128	12	35A61-1128	10
	推动省力 Starting Thrust	适中 Medium	130 ± 30N			5"	48	350	35A65-1129	10	35A63-1129	10	35A64-1129	8
	静音效果 Silent running	优秀 Very Good	6"			50	420	35A68-1130	8	35A66-1130	8	35A67-1130	7	
	耐磨程度 Wearable Level	顶级 Excellent	8"			50	450	35A71-1131	5	35A69-1131	5	35A70-1131	5	
	轮面硬度 Tire Hardness	适中 Medium	95 ± 3A°	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	5"	48	340	35A65-1136	10	35A63-1136	10	35A64-1136	8
	推动省力 Starting Thrust	优秀 Very Good	135 ± 65N			6"	48	410	35A68-1137	8	35A66-1137	8	35A67-1137	7
	静音效果 Silent running	优秀 Very Good	8"			48	430	35A71-1138	5	35A69-1138	5	35A70-1138	5	
	耐磨程度 Wearable Level	顶级 Excellent												

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	145	34	84	148
5"	125	165	38	100.5	151
6"	150	190	44	119	154
8"	200	240	54	154	173



产品特点 Product Features

- 镀锌支架
- 底板、钢碗淬火
- 底板6mm
- 支架6mm
- 可选丝杆方式
- 浇注型聚氨酯工艺
- 高强度聚氨酯
- 性能优良
- Galvanied bracket
- Quenched ball track & top plate
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- Optional thread-stem
- Casting process of PU
- High quality PU
- Excellent performance

选配轮片 Optional Wheels




35A 系列 SERIES

重型 (淬火底板) Heavy Duty (Quenched Ball Track)

安装尺寸 Installation Drawing

平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"
140-400 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
PUPA 	轮面硬度 Tire Hardness	●●●●● 适中 Medium	一体轴承 Annular Ball Bearing	4"	45	250	35A62-1104	15	35A60-1104	15	35A61-1104	10
	推动省力 Starting Thrust	■ ■ ■ ■ ■ 优秀 Very Good		5"	48	300	35A65-1105	12	35A63-1105	12	35A64-1105	8
	静音效果 Silent running	■ ■ ■ ■ ■ 优秀 Very Good		6"	50	350	35A68-1106	8	35A66-1106	8	35A67-1106	7
	耐磨程度 Wearable Level	■ ■ ■ ■ ■ 顶级 Excellent		8"	50	400	35A71-1107	5	35A69-1107	5	35A70-1107	5
RBNB 	轮面硬度 Tire Hardness	●●●●● 软 Very Soft	双滚珠 Ball bearing	5"	50	220	35A65-1408	12	35A63-1408	12	35A64-1408	8
	推动省力 Starting Thrust	■ ■ ■ ■ ■ 适中 Medium		6"	50	280	35A68-1409	8	35A66-1409	8	35A67-1409	7
RBNB 	轮面硬度 Tire Hardness	●●●●● 软 Very Soft	双滚珠 Ball bearing	5"	50	220	35A65-1546	12	35A63-1546	12	35A64-1546	8
	推动省力 Starting Thrust	■ ■ ■ ■ ■ 适中 Medium		6"	50	280	35A68-1547	8	35A66-1547	8	35A67-1547	7
RBCB 	轮面硬度 Tire Hardness	●●●●● 软 Very Soft	双滚珠 Ball bearing	5"	48	220	35A65-1146	10	35A63-1146	10	35A64-1146	8
	推动省力 Starting Thrust	■ ■ ■ ■ ■ 适中 Medium		6"	48	300	35A68-1147	8	35A66-1147	8	35A67-1147	7
	静音效果 Silent running	■ ■ ■ ■ ■ 顶级 Excellent		8"	48	320	35A71-1148	5	35A69-1148	5	35A70-1148	5
TEPB 	轮面硬度 Tire Hardness	●●●●● 软 Very Soft	双滚珠 Ball bearing	4"	50	140	35A62-1531	15	35A60-1531	15	35A61-1531	10
	推动省力 Starting Thrust	■ ■ ■ ■ ■ 一般 Medium		5"	50	180	35A65-1532	12	35A63-1532	12	35A64-1532	8
	静音效果 Silent running	■ ■ ■ ■ ■ 顶级 Excellent		6"	50	230	35A68-1533	8	35A66-1533	8	35A67-1533	7
	耐磨程度 Wearable Level	■ ■ ■ ■ ■ 优秀 Very Good		8"	50	280	35A71-1534	5	35A69-1534	5	35A70-1534	5

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	145	34	84	148
5"	125	165	38	100.5	151
6"	150	190	44	119	154
8"	200	240	54	154	173




产品特点 Product Features

- 镀锌支架
- 底板、钢碗淬火
- 底板6mm
- 支架6mm
- 可配丝杆方式
- 热塑性弹性体注塑而成
- 无噪音
- 保护地面, 不留痕迹
- Galvanied bracket
- Quenched ball track & top plate
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- Optional thread-stem
- Injection with TPE
- Silent running
- Floor-protective, traceless

35A 系列 SERIES 重型 (淬火底板) Heavy Duty (Quenched Ball Track)

安装尺寸 Installation Drawing

平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"
280-440 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
PP-B 	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 一般 Medium 耐磨程度 Wearable Level: 一般 Medium	聚丙烯 Polypropylene	双滚珠 Ball bearing	4"	46	280	35A62-1297	15	35A60-1297	15	35A61-1297	10
				5"	46	340	35A65-1298	12	35A63-1298	12	35A64-1298	8
				6"	48	400	35A68-1299	8	35A66-1299	8	35A67-1299	7
				8"	48	440	35A71-1300	5	35A69-1300	5	35A70-1300	5
NLPA 	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 一般 Medium 耐磨程度 Wearable Level: 优秀 Very Good	塑芯尼龙 Nylon on plastic core	一体轴承 Annular Ball Bearing	4"	45	220	35A62-1112	15	35A60-1112	15	35A61-1112	10
				5"	48	300	35A65-1113	12	35A63-1113	12	35A64-1113	8
				6"	50	370	35A68-1114	8	35A66-1114	8	35A67-1114	7
				8"	50	400	35A71-1115	5	35A69-1115	5	35A70-1115	5
PUPB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	烽火聚氨酯 Polyurethane on plastic core	双滚珠 Ball bearing	5"	50	280	35A74-1117	12	35A72-1117	12	35A73-1117	8
				6"	50	320	35A77-1118	8	35A75-1118	8	35A76-1118	7
				8"	50	350	35A80-1119	5	35A78-1119	5	35A79-1119	5
PUPB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	防滑聚氨酯 Polyurethane on plastic core	双滚珠 Ball bearing	5"	50	280	35A74-1121	12	35A72-1121	12	35A73-1121	8
				6"	50	320	35A77-1122	8	35A75-1122	8	35A76-1122	7
				8"	50	350	35A80-1123	5	35A78-1123	5	35A79-1123	5

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	145	34	84	148
5"	125	165	38	100.5	151
6"	150	190	44	119	154
8"	200	240	54	154	173




产品特点 Product Features

- 镀锌支架(烽火、防滑彩镀)
- 底板、钢碗淬火
- 底板6mm
- 支架6mm
- 可配丝杆方式
- 性能优良
- 耐磨耐用
- Galvanied bracket
- Quenched ball track & top plate
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- Optional thread-stem
- Excellent performance
- Durable & wearable

35A 系列 SERIES 重型 (淬火底板) Heavy Duty (Quenched Ball Track)

安装尺寸 Installation Drawing

平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"

300-460 Kg

产品图片 Product image	性能参数 Performance parameters			轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
 CICB	轮面硬度 Tire Hardness	硬 Very Hard	> 100D	铸铁 Cast iron	双滚珠 Ball bearing	5"	48	380	35A65-1125	10	35A63-1125	10	35A64-1125	8
	推动省力 Starting Thrust	顶级 Excellent	130 ± 20N			6"	50	450	35A68-1126	8	35A66-1126	8	35A67-1126	7
	静音效果 Silent running	较差 Poor	8"			50	460	35A71-1127	5	35A69-1127	5	35A70-1127	5	
	耐磨程度 Wearable Level	较差 Poor												
 PA-B	轮面硬度 Tire Hardness	硬 Very Hard	85D ± 3	酚醛 Phenolic aldehyde	双滚珠 Ball bearing	4"	44	300	35A62-1142	15	35A60-1142	15	35A61-1142	10
	耐磨程度 Wearable Level	优秀 Very Good	50 ± 20N			5"	44	350	35A65-1143	12	35A63-1143	12	35A64-1143	8
	耐温性能 High-Temp Endurance	优秀 Very Good	-25℃ ~ +200℃			6"	44	400	35A68-1144	8	35A66-1144	8	35A67-1144	7
	地面保护 Floor-protection	一般 Medium	8"			44	430	35A71-1145	5	35A69-1145	5	35A70-1145	5	
 NH-B	轮面硬度 Tire Hardness	硬 Very Hard	75D ± 3	高温尼龙 High temperature nylon	双滚珠 Ball bearing	4"	44	300	35A62-1669	15	35A60-1669	15	35A61-1669	10
	耐磨程度 Wearable Level	优秀 Very Good	50 ± 20N			5"	44	350	35A65-1670	12	35A63-1670	12	35A64-1670	8
	耐温性能 High-Temp Endurance	顶级 Excellent	-25℃ ~ +280℃			6"	44	400	35A68-1671	8	35A66-1671	8	35A67-1671	7
	地面保护 Floor-protection	一般 Medium	8"			44	430	35A71-1672	5	35A69-1672	5	35A70-1672	5	

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	145	34	84	148
5"	125	165	38	100.5	151
6"	150	190	44	119	154
8"	200	240	54	154	173




产品特点 Product Features

- 镀锌支架
- 底板、钢碗淬火
- 底板6mm
- 支架6mm
- 可配丝杆方式
- 耐高温
- 适用高温烘焙
- Galvanied bracket
- Quenched ball track & top plate
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- Optional thread-stem
- High-temp durable
- Suitable for bakery room



35C 系列 SERIES 重型 (经济型) Heavy Duty(Economical)

安装尺寸 Installation Drawing



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"
140-400 Kg

 产品图片 Product image	 性能参数 Performance parameters			 轮面材质 Wheel Material	 轮片轴承 Bearing	 轮片直径 (inch) Wheel Diameter	 轮面宽度 (mm) Tire width	 载重 (kg) Capacity	 平底固定 Rigid	 装箱数 PCs/CTN	 平底活动 Swivel	 装箱数 PCs/CTN	 平底刹车 Swivel with brake	 装箱数 PCs/CTN	 尼龙刹车 Swivel with brake	 装箱数 PCs/CTN	 边刹 Swivel with side brake	 装箱数 PCs/CTN
 	轮面硬度 Tire Hardness	适中 Medium	95 ± 3A°	聚氨酯 Polyurethane on plastic core	一体轴承 Annular Ball Bearing	4"	45	250	35C04-1104	15	35C01-1104	15	35C20-1104	10	35C65-1104	10	35C03-1104	10
	推动省力 Starting Thrust	优秀 Very Good	110 ± 40N			5"	48	300	35C08-1105	12	35C05-1105	12	35C21-1105	8	35C66-1105	8	35C07-1105	8
	静音效果 Silent running	优秀 Very Good				6"	50	350	35C12-1106	8	35C09-1106	8	35C22-1106	7	35C67-1106	7	35C11-1106	7
	耐磨程度 Wearable Level	顶级 Excellent				8"	50	400	35C16-1107	5	35C13-1107	5	35C23-1107	5	35C68-1107	5	35C15-1107	5
 	轮面硬度 Tire Hardness	硬 Very Hard	75D ± 3	聚丙烯 Polypropylene	双滚珠 Ball bearing	4"	42	250	35C04-1152	15	35C01-1152	15	35C20-1152	10	35C65-1152	10	35C03-1152	10
	推动省力 Starting Thrust	顶级 Excellent	110 ± 30N			5"	45	300	35C08-1153	12	35C05-1153	12	35C21-1153	8	35C66-1153	8	35C07-1153	8
	静音效果 Silent running	一般 Medium				6"	45	350	35C12-1154	8	35C09-1154	8	35C22-1154	7	35C67-1154	7	35C11-1154	7
	耐磨程度 Wearable Level	一般 Medium				8"	45	400	35C16-1155	5	35C13-1155	5	35C23-1155	5	35C68-1155	5	35C15-1155	5
 	轮面硬度 Tire Hardness	较软 Soft	80 ± 3A	人造胶 Thermoplastic elastomer on plastic core	双滚珠 Ball bearing	4"	50	140	35C04-1633	15	35C01-1633	15	35C20-1633	10	35C65-1633	10	35C03-1633	10
	推动省力 Starting Thrust	一般 Medium	110 ± 30N			5"	50	180	35C08-1634	12	35C05-1634	12	35C21-1634	8	35C66-1634	8	35C07-1634	8
	静音效果 Silent running	顶级 Excellent				6"	50	230	35C12-1635	8	35C09-1635	8	35C22-1635	7	35C67-1635	7	35C11-1635	7
	耐磨程度 Wearable Level	优秀 Very Good				8"	50	280	35C16-1636	5	35C13-1636	5	35C23-1636	5	35C68-1636	5	35C15-1636	5

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	145	34	84	148
5"	125	165	38	100.5	148.5
6"	150	190	44	119	150
8"	200	240	54	154	163



产品特点 Product Features

- 镀锌支架 • Galvanied bracket
- 底板6mm • Thickness of top plate 6mm
- 支架6mm • Thickness of bracket 6mm
- 可选丝杆方式 • Optional thread-stem

抗冲击型 Shock Resistant

- 35B重型抗冲击 Heavy Duty (Shock Resistant)



4"-12"

300-1300 Kg


- 高载重、抗冲击性能强，适用行业范围广

High load bearing, strong impact resistance, wide range of industries.

35B 系列 SERIES 重型抗冲击 Heavy Duty (Shock Resistant)

安装尺寸 Installation Drawing

平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"
300-1200 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
PUCB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	4"	45	380	35B27-0128	8	35B26-0128	8	35B28-0128	8
				5"	48	480	35B03-0129	7	35B01-0129	7	35B02-0129	7
				6"	50	580	35B06-0130	6	35B04-0130	6	35B05-0130	6
				8"	50	720	35B09-0131	5	35B07-0131	5	35B08-0131	5
				10"	62	980	35B12-0201	2	35B10-0201	2	35B11-0201	2
				12"	62	1200	35B15-0202	2	35B13-0202	2	35B14-0202	2
PUCB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	5"	48	430	35B03-1136	7	35B01-1136	7	35B02-1136	7
				6"	48	530	35B06-1137	6	35B04-1137	6	35B05-1137	6
				8"	48	650	35B09-1138	5	35B07-1138	5	35B08-1138	5
CICB 	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 较差 Poor 耐磨程度 Wearable Level: 较差 Poor	铸铁 Cast iron	双滚珠 Ball bearing	5"	50	600	35B03-1125	7	35B01-1125	7	-	-
				6"	50	700	35B06-1126	6	35B04-1126	6	-	-
				8"	50	800	35B09-1127	5	35B07-1127	5	-	-
RBCB 	轮面硬度 Tire Hardness: 软 Very Soft 推动省力 Starting Thrust: 适中 Medium 静音效果 Silent running: 顶级 Excellent 耐磨程度 Wearable Level: 顶级 Excellent	铁芯橡胶 Rubber on cast iron core	双滚珠 Ball bearing	5"	48	300	35B03-1146	7	35B01-1146	7	35B02-1146	7
				6"	48	350	35B06-1147	6	35B04-1147	6	35B05-1147	6
				8"	48	400	35B09-1148	5	35B07-1148	5	35B08-1148	5

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	150	34	84	151
5"	125	175	34	96.5	151
6"	150	200	38	113	151
8"	200	248	47	147	175
10"	250	305	60	185	185
12"	300	355	60	210	210



产品特点 Product Features

- 喷塑支架
- 4-8寸底板10mm
- 10-12寸底板12mm
- 支架8mm
- 底板采用平面压力轴承
- 性能优良
- 抗冲击
- Powder bracket
- 4"-8"Thickness of top plate10mm
- 10"-12"Thickness of top plate12mm
- Thickness of bracket 8mm
- Tapered bearing
- Excellent performance
- Anti shock


选配轮片 Optional Wheels



35B 系列 SERIES 重型抗冲击 Heavy Duty (Shock Resistant)

安装尺寸 Installation Drawing


平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster



产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
NLCB 2 	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 一般 Medium 耐磨程度 Wearable Level: 优秀 Very Good	75D ± 3	110 ± 30N	铁芯尼龙 Nylon on cast iron core	双滚珠 Ball bearing	5"	48	600	35B03-1149	7	35B01-1149	7
						6"	50	700	35B06-1150	6	35B04-1150	6
						8"	50	850	35B09-1151	5	35B07-1151	5
						10"	62	1100	35B12-1209	2	35B10-1209	2
						12"	62	1300	35B15-1210	2	35B13-1210	2
NL-B 2 	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 一般 Medium 耐磨程度 Wearable Level: 优秀 Very Good	75D ± 3	100 ± 30N	超级尼龙 Nylon	双滚珠 Ball bearing	4"	46	450	35B27-1645	7	35B26-1645	7
						5"	46	650	35B03-1646	7	35B01-1646	7
						6"	48	850	35B06-1647	6	35B04-1647	6
						8"	48	1050	35B09-1648	5	35B07-1648	5
MP-B 	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 一般 Medium 耐磨程度 Wearable Level: 适中 Medium	75D ± 3	110 ± 30N	改性PP Modified polypropylene	双滚珠 Ball bearing	5"	50	500	35B03-1394	7	35B01-1394	7
						6"	50	600	35B06-1395	6	35B04-1395	6
						8"	50	700	35B09-1396	5	35B07-1396	5

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	150	34	84	151
5"	125	175	34	96.5	151
6"	150	200	38	113	151
8"	200	248	47	147	175
10"	250	305	60	185	185
12"	300	355	60	210	210



产品特点 Product Features

- 喷塑支架
- 4-8寸底板10mm
- 10-12寸底板12mm
- 支架8mm
- 底板采用平面压力轴承
- 性能优良
- 抗冲击
- Powder bracket
- 4"-8"Thickness of top plate10mm
- 10"-12"Thickness of top plate12mm
- Thickness of bracket 8mm
- Tapered bearing
- Excellent performance
- Anti shock



申牌万向轮
SHENPAI Caster
—SINCE 1993—

超重型 Super Heavy Duty

- 40A超重型 (单轮)
Super Heavy Duty(Single Wheel)
- 40B超重型 (双轮)
Super Heavy Duty(Double Wheels)



3"-12"

1000-5000 Kg

- 适用于重型机械设备，工厂搬运等行业，高品质、高承载


It is suitable for heavy machinery and equipment, factory transportation and other industries, high quality and high load.

40A 系列 SERIES


超重型 (单轮) Super Heavy Duty(Single Wheel)

安装尺寸 Installation Drawing

平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




6-12"
1000-2500 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN
NLCT PUCB PUCB 	轮面硬度 Tire Hardness 推动省力 Starting Thrust 静音效果 Silent running 耐磨程度 Wearable Level	铁芯尼龙 Nylon on cast iron core	锥形轴承 Tapered bearing	6"	64	1300	40A02-1164	4	40A01-1164	4	40A13-1164	3	40A27-1164	3
				8"	64	1600	40A04-1165	2	40A03-1165	2	40A14-1165	2	40A28-1165	2
				10"	80	2000	40A06-1166	2	40A05-1166	2	40A15-1166	2	40A29-1166	2
				12"	80	2500	40A20-1167	2	40A19-1167	2	40A21-1167	2	-	2
PUCB PUCB PUCB 	轮面硬度 Tire Hardness 推动省力 Starting Thrust 静音效果 Silent running 耐磨程度 Wearable Level	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	6"	64	1000	40A02-1156	4	40A01-1156	4	40A13-1156	3	40A27-1156	3
				8"	64	1100	40A04-1157	2	40A03-1157	2	40A14-1157	2	40A28-1157	2
				10"	80	1500	40A06-1158	2	40A05-1158	2	40A15-1158	2	40A29-1158	2
				12"	80	2000	40A20-1159	2	40A19-1159	2	40A21-1159	2	-	2
PUCB PUCB PUCB 	轮面硬度 Tire Hardness 推动省力 Starting Thrust 静音效果 Silent running 耐磨程度 Wearable Level	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	6"	64	1000	40A02-1160	4	40A01-1160	4	40A13-1160	3	40A27-1160	3
				8"	64	1100	40A04-1161	2	40A03-1161	2	40A14-1161	2	40A28-1161	2
				10"	80	1500	40A06-1162	2	40A05-1162	2	40A15-1162	2	40A29-1162	2
				12"	80	2000	40A20-1163	2	40A19-1163	2	40A21-1163	2	-	2

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
6"	150	205	50	125	260
8"	200	255	52	152	260
10"	250	310	52	177	275
12"	300	360	62	212	-



产品特点 Product Features




- 喷塑支架
- 底板采用平面压力及锥形轴承
- 载重大且转动灵活
- 抗冲击, 防腐
- 板材厚度
- Powder bracket
- Tapered bearing
- Easier to swirl while loaded
- Anti shock
- Thickness of steel plate

尺寸 Wheel Size	底板厚度 Thickness of top plate	支架厚度 Thickness of bracket
6"	10mm	8mm
8"	10mm	10mm
10"-12"	15mm	14mm




40B 系列 超重型 (双轮) Super Heavy Duty(Double Wheels)

安装尺寸 Installation Drawing

平底活动/ 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster




3-12"
1700-5000 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN
NL-B	轮面硬度 Tire Hardness	联体尼龙 Nylon	双滚珠 Ball bearing	3"	40	1700	40B27-1548	6	40B26-1548	6	-	-
	推动省力 Starting Thrust			4"	40	2000	40B30-1549	4	40B29-1549	4	-	-
	静音效果 Silent running			5"	40	2300	40B33-1550	2	40B32-1550	2	-	-
	耐磨程度 Wearable Level											
NLCT	轮面硬度 Tire Hardness	铁芯尼龙 Nylon on cast iron core	锥形轴承 Tapered bearing	6"	64	2500	40B02-1164	2	40B01-1164	2	40B22-1164	2
	推动省力 Starting Thrust			8"	64	3500	40B04-1165	1	40B03-1165	1	40B23-1165	1
	静音效果 Silent running			10"	80	5000	40B06-1166	1	40B05-1166	1	40B24-1166	1
	耐磨程度 Wearable Level			12"	80	5000	40B20-1167	1	40B19-1167	1	-	1
PUCB	轮面硬度 Tire Hardness	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	6"	64	1800	40B02-1156	2	40B01-1156	2	40B22-1156	2
	推动省力 Starting Thrust			8"	64	2200	40B04-1157	1	40B03-1157	1	40B23-1157	1
	静音效果 Silent running			10"	80	3000	40B06-1158	1	40B05-1158	1	40B24-1158	1
	耐磨程度 Wearable Level			12"	80	3500	40B20-1159	1	40B19-1159	1	-	1
PUCB	轮面硬度 Tire Hardness	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	6"	64	1800	40B02-1160	2	40B01-1160	2	40B22-1160	2
	推动省力 Starting Thrust			8"	64	2200	40B04-1161	1	40B03-1161	1	40B23-1161	1
	静音效果 Silent running			10"	80	3000	40B06-1162	1	40B05-1162	1	40B24-1162	1
	耐磨程度 Wearable Level			12"	80	3500	40B20-1163	1	40B19-1163	1	-	1

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
3"	75	125	50	87.5	-
4"	100	150	60	110	-
5"	125	175	60	122.5	-
6"	150	205	50	125	260
8"	200	255	52	152	260
10"	250	350	75	200	275
12"	300	405	75	225	-



产品特点 Product Features

- 喷塑支架
- 底板采用平面压力轴承
- 载重大且转动灵活
- 抗冲击
- Powder bracket
- Tapered bearing
- Easier to swirl while loaded
- Anti shock

尺寸 Wheel Size	底板厚度 Thickness of top plate	支架厚度 Thickness of bracket
3"-5"	10mm	10mm
6"	10mm	8mm
8"	10mm	10mm
10"-12"	22mm	14mm



申牌万向轮
SHENPAI Caster
—SINCE 1993—

减震型 Shockproof

- 45A减震型
Shockproof
- 45C减震型 (经济型)
Shockproof (Economical)



5"-8"

300-550 Kg

- 适用于机械制造, 汽车工业等行业, 有减震功效


It is suitable for machinery manufacturing, automobile industry and other industries.

融合标准



45A 系列 SERIES 减震型 Shockproof

安装尺寸 Installation Drawing



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"
300-550 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN
PUCB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	5"	48	360	45A02-0129	5	45A01-0129	5	45A19-0129	3
				6"	50	440	45A04-0130	4	45A03-0130	4	45A20-0130	3
				8"	50	550	45A06-0131	4	45A05-0131	4	45A21-0131	3
PUCB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	5"	48	340	45A02-1136	5	45A01-1136	5	45A19-1136	3
				6"	48	420	45A04-1137	4	45A03-1137	4	45A20-1137	3
				8"	48	480	45A06-1138	4	45A05-1138	4	45A21-1138	3
RBCB 	轮面硬度 Tire Hardness: 软 Very Soft 推动省力 Starting Thrust: 适中 Medium 静音效果 Silent running: 顶级 Excellent 耐磨程度 Wearable Level: 顶级 Excellent	铁芯橡胶 Rubber on cast iron core	双滚珠 Ball bearing	5"	48	300	45A02-1146	5	45A01-1146	5	45A19-1146	3
				6"	48	350	45A04-1147	4	45A03-1147	4	45A20-1147	3
				8"	48	400	45A06-1148	4	45A05-1148	4	45A21-1148	3

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
5"	125	185	50	112.5	190
6"	150	197	50	125	190
8"	200	247	63	163	208



产品特点 Product Features

- 喷塑支架 双弹簧
- 底板6mm
- 支架6mm
- 牵引搬运时顺畅转动及平稳
- Spray coated, twin springs
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- Smooth running while towed


选配刹车/轮片 Optional Brakes/wheels



尺寸 Wheel Size	编码 No.
5"	45A16
6"	45A17
8"	45A18

45C 系列 SERIES 减震型 (经济型) Shockproof (Economical)

安装尺寸
Installation Drawing



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




5-8"
300-550 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN	平底刹车 Swivel with brake	装箱数 PCs/CTN
PUCB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	5"	48	360	45C02-0129	5	45C01-0129	5	45C10-0129	3
				6"	50	440	45C05-0130	4	45C04-0130	4	45C11-0130	3
				8"	50	550	45C08-0131	4	45C07-0131	4	45C12-0131	3
PUCB 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	双滚珠 Ball bearing	5"	48	340	45C02-1136	5	45C01-1136	5	45C10-1136	3
				6"	48	420	45C05-1137	4	45C04-1137	4	45C11-1137	3
				8"	48	480	45C08-1138	4	45C07-1138	4	45C12-1138	3
RBCB 	轮面硬度 Tire Hardness: 软 Very Soft 推动省力 Starting Thrust: 适中 Medium 静音效果 Silent running: 顶级 Excellent 耐磨程度 Wearable Level: 顶级 Excellent	铁芯橡胶 Rubber on cast iron core	双滚珠 Ball bearing	5"	48	300	45C02-1146	5	45C01-1146	5	45C10-1146	3
				6"	48	350	45C05-1147	4	45C04-1147	4	45C11-1147	3
				8"	48	400	45C08-1148	4	45C07-1148	4	45C12-1148	3

外形尺寸
Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
5"	125	185	50	112.5	190
6"	150	197	50	125	190
8"	200	247	63	163	208



产品特点
Product Features

- 镀锌支架 单弹簧
- 底板6mm
- 支架6mm
- 牵引搬运时顺畅转动及平稳
- Galvanized bracket, Single spring
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- Smooth running while towed

选配刹车/轮片
Optional Brakes/wheels



尺寸 Wheel Size	编码 No.
5"	45C03
6"	45C06
8"	45C09



申牌万向轮
SHENPAI Caster
—SINCE 1993—

不锈钢脚轮 Stainless Steel Series

- 10D 不锈钢(微型)
Stainless Steel(Micro Duty)
- 20D 不锈钢(中型)
Stainless Steel(Medium Duty)
- 35D 不锈钢(重型)
Stainless Steel(Heavy Duty)



1.5"-8"

10-350 Kg

- 适用于食品加工等行业，防水、防锈
It is suitable for food processing and other industries.

融合标准




10D


系列
SERIES

不锈钢(微型)
Stainless Steel(Micro Duty)


安装尺寸
Installation Drawing



平底活动 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem




1.5-2"
30-50 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN
TEPS 	轮面硬度 Tire Hardness	人造胶 Thermoplastic elastomer on plastic core	单滚珠 Single ball bearing	1.5"	20	30	10D02-1631	300	10D01-1631	300	10D03-1631	250	10D04-1631	300	10D05-1631	250
	耐磨程度 Wearable Level			2"	22	50	10D07-1632	150	10D06-1632	150	10D08-1632	100	10D09-1632	150	10D10-1632	100
NL-S 	轮面硬度 Tire Hardness	尼龙 Nylon	单滚珠 Single ball bearing	1.5"	20	30	10D02-1629	300	10D01-1629	300	10D03-1629	250	10D04-1629	300	10D05-1629	250
	耐磨程度 Wearable Level			2"	22	50	10D07-1630	150	10D06-1630	150	10D08-1630	100	10D09-1630	150	10D10-1630	100

外形尺寸
Overall Dimensions

尺寸	轮径	平底全高	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	H	F	r	R
1.5"	40	60	67	25	45	67
2"	50	70	77	23	48	67




产品特点
Product Features


- 304不锈钢支架
- 底板厚度2mm
- 支架厚度2mm
- 防锈耐腐蚀
- 304 Stainless steel bracket
- Thickness of top plate 2mm
- Thickness of bracket 2mm
- Antirust & anti-corrosion

20D 系列 Stainless Steel(Medium Duty)


安装尺寸 Installation Drawing



平底活动 刹车底板
Plate of Swivel Caster



平底固定底板
Plate of Rigid Caster



丝杆
Threaded Stem




3-5"
80-150 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN	丝杆活动 Threaded stem swivel	装箱数 PCs /CTN	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs /CTN
TEPS 	轮面硬度 Tire Hardness	●●●●● 软 Soft 人造胶 Thermoplastic elastomer on plastic core	单滚珠 Single ball bearing	3"	32	80	20D15-1375	30	20D01-1375	30	20D02-1375	30	20D13-1375	30	20D14-1375	30
	耐磨程度 Wearable Level			4"	32	90	20D16-1377	25	20D07-1377	25	20D08-1377	25	20D15-1377	25	20D16-1377	25
	静音效果 Silent running			5"	32	95	20D17-1378	15	20D10-1378	15	20D11-1378	15	20D17-1378	15	20D18-1378	15
	地面保护 Floor-protection															
PP-D 	轮面硬度 Tire Hardness	●●●●● 硬 Very Hard 聚丙烯 Polypropylene	特尔灵 Derlin	3"	30	105	20D15-1379	30	20D01-1379	30	20D02-1379	30	20D13-1379	30	20D14-1379	30
	耐磨程度 Wearable Level			4"	32	135	20D16-1380	25	20D07-1380	25	20D08-1380	25	20D15-1380	25	20D16-1380	25
	静音效果 Silent running			5"	32	145	20D17-1381	15	20D10-1381	15	20D11-1381	15	20D17-1381	15	20D18-1381	15
	地面保护 Floor-protection															
PUPB 	轮面硬度 Tire Hardness	●●●●● 适中 Medium 聚氨酯 Polyurethane on plastic core	双滚珠 Ball bearing	3"	32	110	20D15-1388	30	20D01-1388	30	20D02-1388	30	20D13-1388	30	20D14-1388	30
	耐磨程度 Wearable Level			4"	32	140	20D16-1389	25	20D07-1389	25	20D08-1389	25	20D15-1389	25	20D16-1389	25
	静音效果 Silent running			5"	32	150	20D17-1390	15	20D10-1390	15	20D11-1390	15	20D17-1390	15	20D18-1390	15
	地面保护 Floor-protection															

外形尺寸 Overall Dimensions

尺寸	轮径	丝杆全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
3"	75	111	40	77.5	120
4"	100	138	40	90	120
5"	125	163	40	102.5	125




产品特点 Product Features

- 304不锈钢支架
- 底板厚度3mm
- 支架厚度3mm
- 防锈耐腐蚀
- 304 Stainless steel bracket
- Thickness of top plate 3mm
- Thickness of bracket 3mm
- Antirust & anti-corrosion

35D 系列 Stainless Steel(Heavy Duty)

安装尺寸 Installation Drawing

平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




4-8"
220-350 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing	轮片直径 (inch) Wheel Diameter	轮面宽度 (mm) Tire width	载重 (kg) Capacity	平底固定 Rigid	装箱数 PCs /CTN	平底活动 Swivel	装箱数 PCs /CTN	平底刹车 Swivel with brake	装箱数 PCs /CTN
PUPD 2 PP-D 	轮面硬度 Tire Hardness	聚氨酯 Polyurethane on plastic core	特尔灵 Derlin	4"	45	220	35D03-1411	15	35D01-1411	15	35D02-1411	10
	推动省力 Starting Thrust			5"	48	260	35D06-1412	12	35D04-1412	12	35D05-1412	8
	静音效果 Silent running			6"	50	320	35D09-1413	8	35D07-1413	8	35D08-1413	7
	耐磨程度 Wearable Level			8"	50	350	35D12-1414	5	35D10-1414	5	35D11-1414	5
	轮面硬度 Tire Hardness	聚丙烯 Polypropylene	特尔灵 Derlin	4"	42	220	35D03-1419	15	35D01-1419	15	35D02-1419	10
	推动省力 Starting Thrust			5"	45	260	35D06-1420	12	35D04-1420	12	35D05-1420	8
	静音效果 Silent running			6"	45	320	35D09-1421	8	35D07-1421	8	35D08-1421	7
	耐磨程度 Wearable Level			8"	45	350	35D12-1422	5	35D10-1422	5	35D11-1422	5

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径	旋转半径
D	D	H	F	r	R
4"	100	145	34	84	141
5"	125	165	38	100.5	141
6"	150	190	44	119	141
8"	200	240	54	154	154



产品特点 Product Features

- 304不锈钢支架
- 底板厚度5mm
- 支架厚度5mm
- 防锈耐腐蚀
- 304 Stainless steel bracket
- Thickness of top plate 5mm
- Thickness of bracket 5mm
- Antirust & anti-corrosion



申牌万向轮
SHENPAI Caster
—SINCE 1993—

特殊用轮 Casters for Speical Occasions

- 56A 静音脚轮 Silent Caster
- 65A 充气轮 Pneumatic Caster
- 65B 发泡轮 Elasticity Foam
- 66A 脚手架轮 Scaffold Caster
- 70A 叉车用轮 Forklift Wheel
- 70B 叉车用轮 Forklift Wheel




4"-12"

100-800 Kg

- 适用于餐饮、尼龙转运车、工厂搬运、仓储物流、机械制造、叉车设备等行业
Suitable for catering, nylon transporter, factory handling, warehousing and logistics, machinery manufacturing, forklift equipment and other industries.


56A 系列 SERIES 静音脚轮 Silent Caster

安装尺寸 Installation Drawing



平底固定底板
Plate of Rigid Caster

尺寸 D	轮径 D	底板尺寸 AxB	孔距 a x b	孔径 Φd
4"	100	115 x 80	80 x 45	9
5"	130	134 x 90	100 x 52	12



平底活动 刹车底板
Plate of Swivel Caster

尺寸 D	轮径 D	底板尺寸 AxB	孔距 a x b	孔径 Φd
4"	100	100 x 100	71 x 71	9
5"	130	110 x 110	80 x 80	12


4-5"
100-120 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing
	轮面硬度 Tire Hardness: 软 Very Soft 75 ± 3A 推动省力 Starting Thrust: 适中 Medium 60 ± 20N 静音效果 Silent running: 顶级 Excellent 耐磨程度 Wearable Level: 顶级 Excellent	橡胶 Rubber on nylon core	双滚珠 Ball bearing

轮片直径(inch) Wheel Diameter	轮面宽度(mm) Tire width	载重(kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN
4"	36	100	56A02-1050	20	56A01-1050	20
5"	38	120	56A04-1051	12	56A03-1051	12

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径
D	D	H	F	r
4"	100	145	30	80
5"	125	175	36	98.5




产品特点 Product Features

- 全尼龙支架
- 底板采用轴承，转动静音灵活
- 高弹橡胶，静音效果好
- Nylon bracket
- Bearing in swivel bracket
- Elastic rubber & silent running

65A 系列 SERIES 充气轮 Pneumatic Caster

安装尺寸 Installation Drawing



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




8-10"
150-170 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing
	轮面硬度 Tire Hardness: 软 Very Soft 65 ± 3A 推动省力 Starting Thrust: 优秀 Very Good 110 ± 30N 静音效果 Silent running: 顶级 Excellent 耐磨程度 Wearable Level: 优秀 Very Good	充气轮 Pneumatic tire on steel plate structure	双滚珠 Ball bearing

轮片直径(inch) Wheel Diameter	轮面宽度(mm) Tire width	载重(kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN
8"	64	150	65A02-1226	6	65A01-1226	6
10"	86	170	65A04-1227	4	65A03-1227	4

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径
D	D	H	F	r
8"	220	256	50	160
10"	260	308	60	190




产品特点 Product Features

- 彩镀锌架 • Colour galvanized
- 底板6mm • Thickness of top plate 6mm
- 支架6mm • Thickness of bracket 6mm
- 弹力静音 • Pneumatic tire
- 胎宽耐用 • Wide tire, durable lifetime

65B 系列 SERIES 发泡轮 Elasticity Foam

安装尺寸 Installation Drawing



平底活动 刹车 / 固定底板
Plate of Swivel / Rigid Caster




6-10"
150-250 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing
RSSB 	轮面硬度 Tire Hardness: 软 Very Soft 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	发泡轮 Rubber on steel plate structure	双滚珠 Ball bearing

轮片直径(inch) Wheel Diameter	轮面宽度(mm) Tire width	载重(kg) Capacity	平底固定 Rigid	装箱数 PCs/CTN	平底活动 Swivel	装箱数 PCs/CTN
6"	55	150	65B02-1502	8	65B01-1502	8
8"	63	200	65B07-1503	5	65B06-1503	5
10"	63	250	65B12-1504	3	65B11-1504	3

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径
D	D	H	F	r
6"	150	190	44	119
8"	200	250	50	150
10"	250	305	60	185




产品特点 Product Features

- 彩镀支架
- 底板6mm
- 支架6mm
- 优质橡胶轮面
- 弹力静音
- Colour galvanized
- Thickness of top plate 6mm
- Thickness of bracket 6mm
- High quality rubber for wheel tread
- Silent running

66A 系列 SERIES 脚手架轮 Scaffold Caster

安装尺寸 Installation Drawing



5-6"
200-380 Kg




产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing
PUSF 	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	钢芯聚氨酯 Polyurethane on steel plate structure	法兰轴承 Flanged ball bearing
RBSF 	轮面硬度 Tire Hardness: 软 Very Soft 推动省力 Starting Thrust: 适中 Medium 静音效果 Silent running: 顶级 Excellent 耐磨程度 Wearable Level: 顶级 Excellent	钢芯橡胶 Rubber on steel plate structure	法兰轴承 Flanged ball bearing

产品 Product	轮片直径(inch) Wheel Diameter	轮面宽度(mm) Tire width	载重(kg) Capacity	丝杆刹车 Threaded stem swivel with brake	装箱数 PCs/CTN
PUSF	5"	35	280	66A03-1054	4
	6"	38	380	66A01-1055	4
RBSF	5"	40	200	66A03-1064	4
	6"	43	250	66A01-1065	4

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距
D	D	H	F
5"	130	169	37
6"	150	192	40



产品特点 Product Features

- 适用于脚手架
- 镀锌支架
- 丝杆长度可选配
- 钢芯骨架，防腐耐用
- Suitable for scaffold
- Galvanized bracket
- Customized stem length
- Steel plate core

70A 系列 SERIES 叉车用轮 Forklift Wheel



产品特点 Product Features

- 适用于叉车 • Suitable for forklift
- 改性材料 • Modified material
- 高载重 • High capacity
- 高耐磨 • Wearable


8-12"
500-800 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing
	轮面硬度 Tire Hardness: 硬 Very Hard 推动省力 Starting Thrust: 顶级 Excellent 静音效果 Silent running: 一般 Medium 耐磨程度 Wearable Level: 一般 Medium	增强聚丙烯 Modified polypropylene	双滚珠 Ball bearing

轮片直径(inch) Wheel Diameter	轮面宽度(mm) Tire width	载重(kg) Capacity	轴承内径 Bearing diameter	轴承外径 Bearing diameter	型号 Order number	装箱数 PCs/CTN
8"	50	500	20	47	70A-1176	20
	50	500	25	52	70A-1175	20
10"	50	600	25	52	70A-1177	10
12"	50	800	25	52	70A-1178	8
	50	800	30	62	70A-1276	8

70B 系列 SERIES 叉车用轮 Forklift Wheel

安装尺寸 Installation Drawing




4"
250 Kg

产品图片 Product image	性能参数 Performance parameters	轮面材质 Wheel Material	轮片轴承 Bearing
	轮面硬度 Tire Hardness: 适中 Medium 推动省力 Starting Thrust: 优秀 Very Good 静音效果 Silent running: 优秀 Very Good 耐磨程度 Wearable Level: 顶级 Excellent	铁芯聚氨酯 Polyurethane on cast iron core	精密滚珠轴承 Precision ball bearing

轮片直径(inch) Wheel Diameter	轮面宽度(mm) Tire width	载重(kg) Capacity	平底活动 Swivel	装箱数 PCs/CTN
4"	40	250	70B01-1637	4

外形尺寸 Overall Dimensions

尺寸	轮径	平底全高	偏心距	旋转半径
D	D	H	F	r
4"	100	154	31	81



产品特点 Product Features

- 喷塑支架 • Powder bracket
- 减震功效, 适合各种复杂路面 • Shock Absorption
- 可调节高度148mm-164mm • Height adjustable from 148 to 164mm
- 运行速度可达6km/h • Running speed upto 6 km/h

99A 99B 系列 地刹器 Floor lock

附件 Accessories

加重型 Strengthened Structure

底板、踏板加厚 Thicker pedal fork
底座弹簧加固 Spring design below

结构合理 Two Pedal Structure

ON/OFF结构 ON/OFF pedals
升降踩踏轻松便利 Easy to operate

底座螺杆链接 Screw Design

可调节高度 Height Adjustable

高弹力橡胶

底盘包用高弹力橡胶，
有效保护地面，
延长使用寿命

Natural Rubber



Floor protective
Durable service time



美国ANSI标准
ANSI Standard



优化结构，不易卡涩
Improved structure
Free to operate





产品图片 Product image	轮片直径(inch) Wheel Diameter	伸长后高度 Raised height	收缩高度 Lower height	型号 Order number	装箱数 PCs/CTN
地刹器 Floor lock	4"	148-138	120	99A23	10
	5"	173-163	149	99A01	8
	6"	195-186	171	99A02	8
	8"	246-236	222	99A03	8



日本JIS标准
JIS Standard



重载设计
High capacity design



产品图片 Product image	轮片直径(inch) Wheel Diameter	伸长后高度 Raised height	收缩高度 Lower height	型号 Order number	装箱数 PCs/CTN
可调节式 日式地刹器 Adjustable Floor lock	4"	145-150	132	99B01	10
	5"	175-180	153	99B02	10
	6"	205-210	170	99B03	10
	8"	250-255	215	99B04	5
固定式 日式地刹器 Fixde Floor lock	4"	145-150	132	99B14	10
	5"	175-180	153	99B15	10
	6"	205-210	170	99B16	10
	8"	250-255	215	99B18	5
重型 日式地刹器 Heavy duty Floor lock	8"	250-280	210	99B22	5

99D 系列 SERIES 手推车 Hand Cart

扶手加有套管 Foam Handle

防滑 冬天保温

人性化设计 Easy to Carry

便携孔设计，便于携带


版面加强 Metal Pipe Strengthened

在加强筋的基础上增加方管

超级静音轮 Silent Caster

推动轻便 低噪音

产品图片 Product image	轮片材质 Wheel Material	型号 Order number	车板尺寸(mm) Platform size	载重 Capacity	装箱数 PCs/CTN
	人造胶 Thermoplastic elastomer on plastic core	99D10	720 × 480	180	2
	聚氨酯 Polyurethane on plastic core	99D11	720 × 480	200	2
	橡胶 Rubber on nylon core	99D16	900 × 600	300	1
	聚氨酯 Polyurethane on plastic core	99D17	900 × 600	300	1



产品图片 Product image	轮片材质 Wheel Material	型号 Order number	车板尺寸(mm) Platform size	载重 Capacity	装箱数 PCs/CTN
	橡胶 Rubber on nylon core	99D25	900 × 600	300	1
	聚氨酯 Polyurethane on plastic core	99D26	900 × 600	300	1
	橡胶 Rubber on nylon core	99D27	900 × 600	300	1
	聚氨酯 Polyurethane on plastic core	99D28	900 × 600	300	1
	橡胶 Rubber on nylon core	99D14	750 × 480	280	1
	橡胶 Rubber on nylon core				

警告 脚轮使用注意事项

请按照注意事项使用脚轮，以免造成不必要的财产损失，人员伤害；牵引请勿超过4km/h,以免影脚轮使用寿命。

安装



安装脚轮时，使用适当的扳手
拧紧螺丝到没有空隙为止



安装丝杆脚轮时，请勿在刹车
后直接用手拧紧固定脚轮

负载



装载时请根据脚轮负载参数实
际荷载，如果负载超过允许负
载，会降低、损坏其性能



请勿偏载，如果偏载，可能
会造成偏载部分脚轮超负载，降
低、损坏其性能

制动



请勿将处于刹车状态下的脚轮
强行移动，刹车系统将会严重
破坏




请勿在倾斜面上，长时间制动
放置不管，一旦滑行，将导致
损失及脚轮性能下降

环境



请避免长时间在酸、碱、盐、
油、水等特殊环境中使用，长
时间金属易腐蚀



请避免在高温，低温，潮湿等
特殊环境种使用，脚轮的性能
会下降，寿命降低

质保



我司持有SHENPAI商标的产品保用壹年，带有支架喷码，轮片钢印高品质款产品保用贰年，违规使用的情况除外，保存不当引起损坏的情况除外(注：聚氨酯类，橡胶类材质属于易降解或易老化材质，此类产品需先进先出，避免老化造成无法使用。)



轮片 4位 钢印



支架 9位 喷码

保养

为获得脚轮更佳的使用效果和使用寿命，建议定期向轴承和珠盘内加油（免维护轴承除外）

WARNING Attention Before Use

Please use casters according to matters needing attention, so as to avoid unnecessary property loss and personnel injury. Do not pull more than 4km/h, so as not to affect the castor's service life.

Installation



When installing casters, tighten the screws with a proper wrench until there is no gap



When installing threaded casters, do not fasten the casters by hand after braking

Load



When loading, please take the actual load according to the caster load parameter. If the load exceeds the allowable load, it will reduce and damage its performance




Do not off-load, if off-load, may cause off-load part of the caster, reduce and damage its performance

Braking



Do not force to move the casters under the brake, the brake system will be seriously damaged



Do not use the brake on the inclined surface for a long time. It will lead to loss and deterioration of caster performance once sliding

Environment



Please avoid long time in acid, alkali, salt, oil, water and other special environment, metal easy to corrode



Please avoid using in the special environment such as high temperature, low temperature and humidity. The performance of casters will decline and the life will be reduced

Quality Assurance



Products bearing "SHENPAI" trademark are guaranteed for 1 year. Products bearing "SHENPAI" trademark and a 4/9-digit code are guaranteed for 2 years. The guarantee above are only available in the condition of use according to the regulations & attentions on the catalogue as well as warnings in the packaging cartons. (Note: polyurethane, rubber material belongs to easily degradable material or aging, such products should be first in first out, avoid aging can't use.)



Traceable code - 4 digits



Traceable code - 9 digits

Maintenance

In order to obtain better effect and service life of casters, it is recommended to oil the bearings and ball discs regularly (except maintenance free bearings).